

CYCLE 2025-07

Sorting order:

A – first 'quotas', then 'suspensions'

B – **new** requests, **amending** requests.

>>>The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group.

Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic<<<

| CN code | TARIC | Reference Mail | Working Number | Description | Quotas | New or amendment request | Measure status | Partner Position Country | Partner Position | Public Comments |
|------------|-------|----------------|----------------|--|---------------------------------|--------------------------|-------------------|--------------------------|------------------|--|
| 2912 29 00 | | 6299867/2024 | 1001 | Cyclohex-3-en-1-carbaldehyde (CAS RN 100-50-5) with a purity of 98 % or more | Q/77tonnes, 01.07-31.12 | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 used for production of as anti-aging rubber additive |
| 2917 39 85 | | 6560149/2024 | 3312 | 1,3-dioxo-1,3-dihydro-2-benzofuran-5-carboxylic acid (CAS RN 552-30-7) with a purity by weight of 97 % or more | Q/4300tonnes, 01.07-31.12 | New | UNDER EXAMINATION | FR | Applicant | Round 2025/7 - for use in the manufacture of trimellitate esters |
| 2918 11 00 | | 6469278/2024 | 1015 | L-(+)-lactic acid (CAS RN 79-33-4) with a purity by weight of 99 % or more | Q/56000tonnes, 01.07-31.12 | New | UNDER EXAMINATION | ES | Applicant | Round 2025/7 |
| 2932 19 00 | | 6819955/2024 | 3356 | Tetrahydro-2-methylfuran (CAS RN 96-47-9) with a purity by weight of 99 % or more | Q/2000000kilograms, 01.07-31.12 | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 to be used in chemical formulation mainly for pharma industry |
| 2933 59 95 | | 6546261/2024 | 3303 | Ametoctradin (CAS RN 865318-97-4) with a purity by weight of 98 % or more | Q/353500kilograms, 01.07-31.12 | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 active ingredient for fungicides |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---------------------------------|-----|-------------------|----|-----------|--|
| 2933 99 80 | | 6469451/2024 | 1016 | L-Tryptophan (CAS RN 73-22-3) with a purity by weight of 98,5 % or more | Q/6000kilograms, 01.07-31.12 | New | UNDER EXAMINATION | ES | Applicant | Round 2025/7 Intended for the manufacture of chemical |
| 3815 19 90 | | 6412686/2024 | 1013 | Catalyst consisting of organo-metallic compounds of boron and titanium, fixed on a support of silicon dioxide, in the form of powder | Q/7800kilograms, 01.07-31.12 | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 used in the manufacturing of polyethylene. |
| 3907 29 20 | | 7015592/2024 | 1044 | Polyether polyol with a total bio content of 35 % and containing by weight <ul style="list-style-type: none"> - 9 % or more but not more than 15 % of palm oil, - 20 % or more but not more than 25 % of sucrose - with a hydroxyl number of 420 or more but not more than 460 and a viscosity index of 3 000 or more but not more than 4 000 | Q/1000000kilograms, 01.07-31.12 | New | UNDER EXAMINATION | TR | Applicant | Round 2025/7 used as Polyurethane Foam Formulation component. |
| 8409 91 00 | | 6838521/2024 | 1042 | Cylinder head blank for a four cylinder engine with 10 cores, made of aluminium alloy EN AC-45500, with: <ul style="list-style-type: none"> - no other components, - a hardness of 52 HRB or more, - casting defects size of not more than 0,4 mm and not more than 10 defects per cm², - a dendrite arm space in combustion chamber of not more than 25 µm, - a double deck water jacket design, - a weight of 14 kg or more but not more than 19 kg, - a length of 506 mm or more but not more than 510 mm, - a height of 282 mm or more but not more than 286 mm and - a width of 143,7 mm or more but not more than 144,3 mm | Q/100000pieces, 01.07-31.12 | New | UNDER EXAMINATION | SE | Applicant | Round 2025/7 used in the manufacture of spark-ignition internal combustion engines for vehicles of tariff heading 8703 |

| | | | | | | | | | | |
|--|----------------------|--------------|-------|---|--------------------------------|-----------|-------------------|--|---|---|
| 8411 99 00 | | 6820127/2024 | 3357 | Turbine ring segments, guide and rotor blades made of nickel-based superalloys, as parts of a stationary gas turbine for power generation or as a mechanical drive | Q/615000kilograms, 01.07-31.12 | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 for installation in gas turbines of CN 84118280 or 84119900 |
| ex 2309 90 31 ex 2309 90 31 ex 2309 90 96 ex 2309 90 96 | 51 59 51 59 | 1995474/2022 | 6003O | Feed additive, consisting on dry weight basis of: - 68 % or more, but not more than 80 % of L-lysine sulphate, and - not more than 32 % of other components such as carbohydrates and other amino acids, for use in the production of animal feed and/or for use in the production of pharmaceuticals (1) | Q/50000tonnes, 01.01-30.06 | Amendment | UNDER EXAMINATION | NL DK EU FR | Applicant Co-applicant Opposed Opposed | Round 2025-07 - review of the quota// |
| ex 2918 22 00 | 10 | 1028/2007 | 6000O | O-acetylsalicylic acid (CAS RN 50-78-2) | Q/120tonnes, 01.01-30.06 | Amendment | UNDER EXAMINATION | PL FR | Applicant Opposed | Round 2025-07 - objection. |
| ex 2922 41 00 | 30 | 2544706/2019 | 6002O | L-Lysine hydrochloride (CAS RN 657-27-2) or an aqueous solution of L-lysine (CAS RN 56-87-1), containing by weight 50 % or more of L-lysine, for use in the production of animal feed and/or for use in the production of pharmaceuticals (1) | Q/150000tonnes, 01.01-30.06 | Amendment | UNDER EXAMINATION | NL AT DK ES PL EU FR | Applicant Co-applicant Co-applicant Co-applicant Opposed Opposed | Round 2025-07 - review of the quota. Round 2025-01 - Compromise - 6 months quota for 50% of the annual volume + end use requirement. Animal feed, either in the form of a pre-mix or as a final product |
| ex 3811 29 00 | 80 | 452962/2013 | 5008 | FR(9.9.2024) amendment: Additives, consisting of 1,3,4-thiadiazolidine-2,5-dithione reaction products with hydrogen peroxide and tert-nonanethiol, containing by weight : - 70 % or more of 2,5-bis(tert-nonyldithio)-[1,3,4]-thiadiazole (CAS RN 89347-09-1), and | Q/500tonnes, 01.01-31.12 | Amendment | UNDER EXAMINATION | FR | Applicant | Round 2025-01 request for amendment. Round 2023-01 - objection. This tariff suspension will be closed and instead a tariff quota for 500 t/year will be open. |

| | | | | | | | | | | | |
|---------------|----|--------------|------|---|---------------------------|------------------|-------------------|----------------------|--|---|---|
| | | | | <p>- 10 % or more of 5-(tert-nonyldithio)- 1,3,4-thiadiazole-2(3H)-thione (CAS RN 97503-12-3), for use in the manufacture of blends of additives for lubricating oils</p> <p>---</p> <p>Current text: Additives containing by weight :</p> <ul style="list-style-type: none"> - 70 % or more of 2,5-bis(tert-nonyldithio)-[1,3,4]-thiadiazole (CAS RN 89347-09-1), and - 10 % or more of 5-(tert-nonyldithio)- 1,3,4-thiadiazole-2(3H)-thione (CAS RN 97503-12-3), for use in the manufacture of blends of additives for lubricating oils <p>(1)</p> | | | | | | | <p>This material is a corrosion inhibitor especially for copper containing metals. It also serves as an antiwear agent or extreme pressure agent, odour controller and oxidation inhibitor. Its purpose is to prevent wear, odour, degradation of the lubricants and destruction of machinery such as gears</p> |
| ex 8482 99 00 | 60 | 4921841/2020 | 6001 | <p>Inner or outer rings made of steel, not hardened or not grinded, outer ring with internal raceway(s), inner ring with external raceway(s), with external diameters of:</p> <ul style="list-style-type: none"> - 14 mm or more but not more than 77 mm for the inner ring, - 26 mm or more but not more than 101 mm for the outer ring, <p>for use in the manufacture of bearings</p> <p>(1)</p> | Q/2000pieces, 01.01-31.12 | Amendment | UNDER EXAMINATION | PT CZ IT TR | Applicant Opposed Opposed Opposed | <p>Round 2025-07 – review of the quota. Round 2025-01 - Round 2021-07 of a kind used for the production of one raceway ball bearing</p> | |

| CN code | TARIC | Reference Mail | Working Number | Description | <u>Suspensions</u> | New or New request | Measure status | Partner Position Country | Partner Position | Public Comments |
|---------|-------|----------------|----------------|-------------|--------------------|--------------------|----------------|--------------------------|------------------|-----------------|
|---------|-------|----------------|----------------|-------------|--------------------|--------------------|----------------|--------------------------|------------------|-----------------|

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|--|
| 2811 22 00 | | 6542070/2024 | 1030 | Silicon dioxide (CAS RN CAS RN 112926-00-8) in powder form with purity by weight of 99 % or more | S | New | UNDER EXAMINATION | TR | Applicant | Round 2025/7 used for radial automobile tire production |
| 2903 99 80 | | 6374666/2024 | 1008 | 4-Bromo-2-fluorobiphenyl (CAS RN 41604-19-7) with a purity by weight of 99 % or more | S | New | UNDER EXAMINATION | IT | Applicant | Round 2025/7 used to produce active pharmaceutical ingredient |
| 2909 49 80 | | 6675369/2024 | 3337 | 2,2'-[oxybis(methylene)]bis[2-ethylpropane-1,3-diol] (CAS RN 23235-61-2) with a purity of 80 % or more by weight | S | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 to be used in the production of a resin for inks, coatings and overprint varnishes |
| 2918 30 00 | | 6674744/2024 | 3336 | Ethyl 4-oxopentanoate (CAS RN 539-88-8) with a purity by weight of 98 % or more | S | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 used as intermediate in the production of a chemical substance |
| 2920 29 00 | | 6700988/2024 | 3346 | UV absorber, containing: - more than 97 % but not more than 99,8 % by weight of <i>Bis</i> (2,4-dicumylphenyl) pentaerythritol diphosphite (CAS RN 154862-43-8) and - more than 0,2 % but not more than 2 % triisopropanol amine | S | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 |
| 2922 29 00 | | 6559853/2024 | 3307 | <i>N,N</i> -bis(4-methoxybenzyl)amine (CAS RN 17061-62-0) with a purity by weight of 96 % or more | S | New | UNDER EXAMINATION | FR | Applicant | 2025/7 - Raw material for the manufacturing of active pharmaceutical ingredients and intermediates |
| 2924 19 00 | | 6569422/2024 | 3313 | Pentanoic acid, 5-(dimethylamino)-2-methyl-5-oxo-,methyl ester (CAS RN 1174627-68-9) with a purity by weight of 70 % or more | S | New | UNDER EXAMINATION | FR | Applicant | Round 2025/7 - for use in the production of fungicides |
| 2924 98 59 | | 6532635/2024 | 1027 | Magnesium 2-aminoacetate (IUPAC) with a purity by weight of 100 % | S | New | UNDER EXAMINATION | IE | Applicant | Round 2025/7 use in the manufacture of |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|--|
| | | | | | | | | | | specific physiological formulations with other ingredient |
| 2925 29 00 | | 1966069/2024 | 1511 | <p>NL 7.5.24 Aqueous solution consisting by weight of:</p> <ul style="list-style-type: none"> - more than 30 % but not more than 36 % of <i>N,N</i>-dibutyl[bis(diethylamino)]methaniminium chloride (CAS RN 89450-30-6) - not more than 14 % of sodium chloride (CAS RN 7647-14-5) <p>---</p> <p>FR 2.5.24 <i>N,N</i>-Dibutyl[bis(diethylamino)]methaniminium chloride (CAS RN 89450-30-6) with a concentration of more than 30 % but not more than 36 % by weight and sodium chloride (CAS RN 7647-14-5) with a concentration not more than 14 % by weight</p> <p>---</p> <p>DK 1.5.24 (supported by IT): Aqueous solution containing by weight 30 % or more, but not more than 36 % of <i>N,N</i>-Dibutyl[bis(diethylamino)]methaniminium chloride (CAS RN 89450-30-6 and by weight not more than 14 % of sodium chloride (CAS RN 7647-14-5)</p> <p>---</p> <p>Dibutyl[<i>bis</i>(diethylamino)]methaniminium chloride (CAS RN 89450-30-6) with a concentration of more than 30 but not more than 36 % by weight and sodium chloride (CAS RN 7647-14-5) with a concentration not more than 14 % by weight</p> | S | New | UNDER EXAMINATION | BE | Applicant | <p>Round 2025-07 - Roll over</p> <p>Round 2025/01. Components for tire industry.</p> |
| 2932 99 00 | | 6560077/2024 | 3311 | 2-butyl-3-(4-hydroxybenzoyl)benzofuran (CAS RN 52490-15-0) with a purity by weight of 99 % or more | S | New | UNDER EXAMINATION | FR | Applicant | Round 2025/7 used for the manufacturing of a drug to treat heart diseases |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|---|
| 2933 39 99 | | 6559820/2024 | 3306 | (R)-(-)-3-amino-1-boc-piperidine (CAS RN 188111-79-7) with a purity by weight of 96 % or more | S | New | UNDER EXAMINATION | FR | Applicant | 2025/7 - Raw material for the manufacturing of active pharmaceuticals ingredients and intermediates |
| 2933 39 99 | | 6559904/2024 | 3308 | 2,4-dichloro-3-nitropyridine (CAS RN 5975-12-2) with a purity by weight of 99 % or more | S | New | UNDER EXAMINATION | FR | Applicant | 2025/7 - raw material for the manufacture of active pharmaceutical ingredients and intermediates |
| 2933 59 95 | | 6559961/2024 | 3309 | Ruxolitinib phosphate (INNM) (CAS RN 1092939-17-7) with a purity by weight of 99 % or more | S | New | UNDER EXAMINATION | FR | Applicant | 2025/7 - substance to be used in the manufacturing of pharmaceutical product |
| 2933 99 80 | | 6501799/2024 | 1022 | <i>N,N</i> -Dimethyl- <i>N</i> -octadecyl-1-octadecanaminium-(sp-4-2)-[29h,31 <i>H</i> -phthalocyanine-2-sulfonato-n29,n30,n31,n32]cuprate(CAS RN 70750-63-9) with a purity by weight of 90 % or more. | S | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 for use in the manufacture of industrial masterbatch. |
| 2933 99 80 | | 6408059/2024 | 1010 | 2-(2 <i>H</i> -Benzotriazole-2-yl)-6-(2-phenylpropane-2-yl)-4-(2,4,4-trimethylpentane-2-yl)phenole (CAS RN 73936-91-1) with a purity by weight of 97 % or more | S | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 used for Light stabilizer for Plastics, paints or Coatings |
| 2933 99 80 | | 6407956/2024 | 1009 | 5 <i>H</i> -Pyrazolo[4,3- <i>c</i>]pyridine-5-carboxylic acid, 3-amino-2-(4-fluoro-3,5-dimethylphenyl)-2,4,6,7-tetrahydro-4-methyl-, 1,1-dimethylethyl ester, (4 <i>S</i>) (CAS RN 2212021-59-3) with a purity by weight of 99 % or more | S | New | UNDER EXAMINATION | IT | Applicant | Round 2025/7 used in the synthesis of intermediates |
| 2933 99 80 | | 6676141/2024 | 3340 | Poly(oxy-1,2-ethanediyl),alpha-[3-[3-(2 <i>H</i> -benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxy-phenyl]-1-oxopropyl]-omega-hydroxy- and poly(oxy-1,2-ethanediyl),alpha-[3-[3-(2 <i>H</i> -benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxy- phenyl]-1-oxopropyl]-omega-[3-[3-(2 <i>H</i> -benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4- | S | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|--|
| | | | | hydroxyphenyl]-1- oxopropoxy] with a purity by weight of 98 % or more | | | | | | |
| 2933 99 80 | | 6700668/2024 | 3342 | 2-(2 <i>H</i> -benzotriazol-2-yl)-6-(1-methyl-1-phenylethyl)-4-(1,1,3,3-tetramethylbutyl) phenol (CAS RN 73936-91-1) with a purity by weight of 99 % or more | S | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 |
| 2933 99 80 | | 6469177/2024 | 1014 | 6- <i>O</i> - <i>tert</i> -butyl 4a- <i>O</i> -methyl (4a <i>R</i>)-1-(4-fluorophenyl)-4,5,7,8-tetrahydropyrazolo[3,4- <i>g</i>]isoquinoline-4a,6-dicarboxylate (CAS RN 864972-21-4) with a purity by weight of 95 % or more | S | New | UNDER EXAMINATION | ES | Applicant | Round 2025/7 used to manufacture a new Active Pharmaceutical Ingredient (NCE New Chemical Entity). |
| 2934 99 90 | | 6704545/2024 | 3350 | <i>Bis</i> -4 <i>H</i> -3,1-benzoxazin-4-one, 2,2'-(1,4-phenylene)-(CAS RN 18600-59-4) | S | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 |
| 2934 99 90 | | 6704858/2024 | 3352 | 2-[4,6- <i>bis</i> ([1,1'-biphenyl]-4-yl))-1,3,5-triazin-2-yl]-5-[(2-ethylhexyl)oxy]phenol (CAS RN 204583-39-1) | S | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 |
| 3204 13 00 | | 6819860/2024 | 3355 | Mixture of: - 25 % or more but not more than 40 % of Colourant C.I. Basic Blue 3 (CAS RN 33203-82-6) and - 25 % or more but not more than 40 % of C.I. Basic Blue 159 (CAS RN 105953-73-9) and preparations based thereon | S | New | UNDER EXAMINATION | TR | Applicant | Round 2025/7 for use in the manufacture of dyed acrylic fiber |
| 3204 15 00 | | 6633361/2024 | 3317 | Vat blue 1 solution containing by weight: - 40 % of a mixture (CAS RN 207692-02-2) of Vat Blue 1 reduced K-salt (CAS RN 835912-68-0) and Na-Salt (CAS RN 894-86-0) in the ratio of 3:2; - 0,5 % of Napthalenesulfonic acid, polymer with formaldehyde, sodium salt (CAS RN 9084-06-4); - 2,4 % of Potassium hydroxide (CAS RN 1310-58-3); - 1,6 % of Sodium hydroxide (FKS) (CAS RN 1310-73-2); | S | New | UNDER EXAMINATION | TR | Applicant | Round 2025/7 - for use in the textile industry |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|--|
| | | | | - 55,5 % of Water (CAS RN 7732-18-5) | | | | | | |
| 3204 17 00 | | 6905336/2024 | 1039 | Colourant C.I. Pigment Yellow 110 (CAS RN 5590-18-1) and preparations based thereon with a colourant C.I. Pigment Yellow 110 content of 90 % or more by weight | S | New | UNDER EXAMINATION | NL | Applicant | Round 2025/7 for use in the manufacture of industrial colourant |
| 3204 17 00 | | 6905292/2024 | 1040 | Colourant C.I. Pigment Yellow 62 (CAS RN 12286-66-7) and preparations based thereon with a colourant C.I. Pigment Yellow 62 content of 90 or more by weight | S | New | UNDER EXAMINATION | NL | Applicant | Round 2025/7 for use in the manufacture of industrial colourant |
| 3204 17 00 | | 6905230/2024 | 1041 | Colourant C.I. Pigment Yellow 17 (CAS RN 4531-49-1) and preparations based thereon with a colourant C.I. Pigment Yellow 17 content of 90 % or more by weight | S | New | UNDER EXAMINATION | NL | Applicant | Round 2025/7 for use in the manufacture of industrial colourant |
| 3204 17 00 | | 6532547/2024 | 1026 | Colourant C.I. Pigment Yellow 13 (CAS RN 5102-83-0) and preparations based thereon with a colourant C.I. Pigment Yellow 13 content of 50 % or more by weight | S | New | UNDER EXAMINATION | IE | Applicant | Round 2025/7 to be used in the manufacturing of a specialty pigment. |
| 3204 17 00 | | 6905393/2024 | 1038 | Colourant C.I. Pigment Yellow 139 (CAS RN 36888-99-0) and preparations based thereon with a colourant C.I. Pigment Yellow 139 content of 90 % or more by weight | S | New | UNDER EXAMINATION | NL | Applicant | Round 2025-07 Pigment Preparation for use in the manufacture of industrial colourant |
| 3204 17 00 | | 6542652/2024 | 3302 | Colourant C.I. Pigment Yellow 174 (CAS n 78952-72-4) and preparations based thereon with a colourant C.I. Pigment Yellow 174 content of 50 % or more by weight. | S | New | UNDER EXAMINATION | IE | Applicant | Round 2025/7 to be used on the manufacturing of a specialty pigment |
| 3204 17 00 | | 6905498/2024 | 1037 | Colourant C.I. Pigment Yellow 147 (CAS RN 4118-16-5) and preparations based thereon with a colourant C.I. Pigment Yellow 147 content of 90 % or more by weight | S | New | UNDER EXAMINATION | NL | Applicant | Round 2025/7 for use in the manufacture of industrial colourant |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|---|
| 3204 17 00 | | 6501729/2024 | 1021 | Colourant C.I. Pigment Red 146 (CAS RN 5280-68-2) and preparations based thereon with a colourant C.I. Pigment Red 146 content of 90 % or more by weight | S | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 for use in the manufacture of industrial colourant. |
| 3204 17 00 | | 6501677/2024 | 1020 | Colourant C.I. Pigment Red 264 (CAS RN 88949-33-1) and preparations based thereon with a colourant C.I. Pigment Red 264 content of 90 % or more by weight | S | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 for use in the manufacture of industrial colourant |
| 3204 17 00 | | 6325899/2024 | 1007 | Colourant C.I. Pigment Red 2 (CAS RN 6041-94-7) and preparations based thereon with a colourant C.I. Pigment Red 2 content of 90 % or more by weight | S | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 for use in the manufacture of industrial colourant. |
| 3204 17 00 | | 6325804/2024 | 1006 | Colourant C.I. Pigment Yellow 65 (CAS RN 6528-34-3) and preparations based thereon with a colourant C.I. Pigment Yellow 65 content of 90 % or more by weight | S | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 for use in the manufacture of industrial colourant. |
| 3204 17 00 | | 6325563/2024 | 1004 | Colourant C.I. Pigment Red 177 (CAS RN 4051-63-2) and preparations based thereon with a colourant C.I. Pigment Red 177 content of 90 % or more by weight | S | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 Pigment raw materials are weighed out together with Polymer carrier according to the formulation and 'staged' for processing |
| 3204 17 00 | | 6701125/2024 | 3348 | Colourant C.I. Pigment Blue 29 (CAS RN 57455-37-5) and preparations based thereon with a colourant C.I. Pigment Blue 29 content of 90 % or more by weight | S | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 for use in the production of industrial colourant |
| 3204 17 00 | | 6905728/2024 | 1033 | Colourant C.I. Pigment Yellow 168 (CAS RN 71832-85-4) and preparations based thereon with a colourant C.I. Pigment Yellow 168 content of 90 % or more by weight | S | New | UNDER EXAMINATION | NL | Applicant | Round 2025/7 for use in the manufacture of industrial colourant |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|---|
| 3204 17 00 | | 6325339/2024 | 1003 | Colourant C.I. Pigment Red 112 (CAS RN 6535-46-2) and preparations based thereon with a colourant C.I. Pigment Red 112 content of 90 % or more by weight | S | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 Pigment raw materials are weighed out together with Polymer carrier according to the formulation and 'staged' for processing |
| 3204 17 00 | | 6704383/2024 | 3349 | Colourant C.I. Pigment Yellow 180 (CAS RN 77804-81-0) and preparations based thereon with a colourant C.I. Pigment Yellow 180 content of 90 % or more by weight | S | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 for use in the manufacture of industrial colourant |
| 3204 17 00 | | 6501301/2024 | 1018 | Colourant C.I. Pigment Red 264 (CAS RN 88949-33-1) and preparations based thereon with a colourant C.I. Pigment Red 264 content of 90 % or more by weight | S | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 manufacture of industrial colourant. |
| 3204 17 00 | | 6299757/2024 | 1000 | Colourant C.I. Pigment Red 122 (CAS RN 980-26-7) and preparations based thereon with a colourant C.I. Pigment Red 122 content of 90 % or more by weight | S | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 for use in the manufacture of industrial colourant |
| 3204 17 00 | | 6325279/2024 | 1002 | Colourant C.I. Pigment Yellow 183 (CAS RN 65212-77-3) and preparations based thereon with a colourant C.I. Pigment Yellow 183 content of 90 % or more by weight | S | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 for use in the manufacture of industrial colourant. |
| 3204 19 00 | | 6905681/2024 | 1034 | Colourant C.I. Solvent Yellow 114 (CAS RN 17772-51-9) and preparations based thereon with a colourant C.I. Solvent Yellow 114 content of 90 % or more by weight | S | New | UNDER EXAMINATION | NL | Applicant | Round 2025/7 for use in the manufacture of industrial colourant |
| 3204 19 00 | | 6905530/2024 | 1036 | Colourant C.I. Solvent Red 52 (CAS RN 81-39-0) and preparations based thereon with a colourant C.I. Solvent Red 52 content of 90 % or more by weight | S | New | UNDER EXAMINATION | NL | Applicant | Round 2025/7 for use in the manufacture of industrial colourant |
| 3204 19 00 | | 6905598/2024 | 1035 | Colourant C.I. Solvent Red 135 (CAS RN 71902-17-5) and preparations based thereon with a | S | New | UNDER EXAMINATION | NL | Applicant | Round 2025/7 for use in the manufacture of industrial colourant |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|--|
| | | | | colourant C.I. Solvent Red 135 content of 90 % or more by weight | | | | | | |
| 3206 49 70 | | 6325697/2024 | 1005 | Colourant C.I. Pigment Yellow 164 (CAS RN 68412-38-4) and preparations based thereon with a colourant C.I. Pigment Yellow 164 content of 90 % or more by weight | S | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 for use in the manufacture of industrial colourant. |
| 3809 91 00 | | 6559753/2024 | 3305 | Water based antimony pentoxide solution containing by weight 25 % or more but not more than 50 % of diantimony pentoxide (CAS RN 1314-60-9) | S | New | UNDER EXAMINATION | TR | Applicant | 2025/7 - Flame retardant to be used in modacrylic fiber |
| 3812 39 10 | | 6700840/2024 | 3345 | Pentaerythritol tetrakis(3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate) (CAS RN 6683-19-8) | S | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 |
| 3812 39 90 | | 6700716/2024 | 3343 | Reaction mass of - decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester and - decanedioic acid, (1,2,2,6,6-pentamethyl-4-piperidiny) methyl ester (CAS RN 1065336-91-5) | S | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 |
| 3812 39 90 | | 6408129/2024 | 1011 | UV stabilizer based on - reaction mass of Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy- and Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy] (CAS RN 400-830-7) with a purity by weight of 55 % or more, but not more than 75 %, - Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacat (CAS RN 41556-26-7) with a purity by weight of 15 % or more, but not more than 35 %, and - Methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacat (CAS RN 82919-37-7) with a | S | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 for the plastics processing industry, paints and lacquers |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|---|
| | | | | purity by weight of 5 % or more, but not more than 15 % | | | | | | |
| 3812 39 90 | | 6408250/2024 | 1012 | UV stabilizer based on a - reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates (CAS RN 127519-17-9) with a purity by weight of 40 % or more, but not more than 60 %, and a - reaction mass of decanedioic acid, 1,10-bis[2,2,6,6-tetramethyl-1-(octyloxy)-4-piperidiny] ester and decanedioic acid, 1,8-octanediy]bis[oxy(2,2,6,6-tetramethyl-1,4-piperidinediyl)] bis[2,2,6,6-tetramethyl-1-(octyloxy)-4-piperidiny] (CAS RN 29757-67-1) with a purity by weight of 40 % or more, but not more than 60 % | S | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 used for UV stabilizer, Additive for the Plastics processing industry, paints and lacquers |
| 3812 39 90 | | 6701073/2024 | 3347 | Ethyl 4-[(methylphenylamino)methylene]amino] benzoate (CAS RN 57834-33-0) with a purity of 99 % or more by weight | S | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 |
| 3812 39 90 | | 6700790/2024 | 3344 | Reaction mass of Octyl-3-[3-tert-butyl-4-hydroxy-5-(5-chloro-2Hbenzotriazole-2-yl) phenyl] propionate (CAS RN 83044-89-7) and 2-Ethylhexyl-3-[3-tert-butyl-4-hydroxy-5-(5-chloro-2H-benzotriazole-2-yl) phenyl] Propionate (CAS RN 83044-90-0) | S | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 |
| 3812 39 90 | | 6675920/2024 | 3339 | Stabiliser containing: - 75 % or more but not more than 95 % by weight of 2-(4,6-bis(2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-hydroxyphenol with ((C10-16, rich in C12-13 alkyloxy) methyl) oxyrane (CAS RN 153519-44-9) and - 5 % or more but not more than 25 % by weight of 1-methoxy-2-propanol (CAS RN 107-98-2) | S | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|---|
| 3812 39 90 | | 6676427/2024 | 3341 | <p>Light stabilisers containing a mixture of</p> <ul style="list-style-type: none"> - benzenepropanoic acid, 3-(2<i>H</i>-benzotriazole-2-yl)-5-(1,1-di-methylethyl)-4-hydroxy-, C7-9 branched and - linear alkyl esters (CAS RN 127519-17-9) in an amount of 92 % or more by weight and 1-methoxy-2-propyl acetate (CAS RN 108-65-6) of more than 2 % but not more than 8 % by weight | S | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 |
| 3815 90 90 | | 6569700/2024 | 3315 | <p>Catalytic preparations for fluid catalytic cracking, in the form of powder, consisting of a mixture of one or more of the following active substances:</p> <ul style="list-style-type: none"> - calcium carbonate (CAS RN 471-34-1), - copper oxide (CAS RN 1217-38-0), - iron oxide (CAS RN 1309-37-1), - aluminium magnesium vanadium oxide (CAS RN 70621-8-0), - aluminium phosphate (CAS RN 7784-30-7), - cerium oxide (CAS RN 1306-38-3), <p>and one or more of the following inert substances:</p> <ul style="list-style-type: none"> - magnesium oxide (CAS RN 1309-48-8), - aluminium oxide (CAS RN 1344-28-1), - kaolin (CAS RN 1332-58-7) | S | New | UNDER EXAMINATION | NL | Applicant | Round 2025/7 - catalytic preparations for use in the refinery of hydrocarbons |
| 3824 99 92 | | 6560008/2024 | 3310 | <p>Mixture containing by weight:</p> <ul style="list-style-type: none"> - 55 % or more but not more than 65 % of (2<i>S</i>,3<i>S</i>,4<i>S</i>,5<i>R</i>,6<i>R</i>)-2-(((2<i>R</i>,3<i>R</i>,5<i>S</i>,6<i>R</i>)-4-(((2<i>R</i>,3<i>S</i>,4<i>S</i>,5<i>R</i>,6<i>R</i>)-3-acetoxy-4,5-bis(benzyloxy)-6-((benzyloxy)methyl)tetrahydro-2<i>H</i>-pyran-2-yl)oxy)-3,5-bis(benzyloxy)-6-(4-methoxy-4-oxobutoxy)tetrahydro-2<i>H</i>-pyran-2-yl)methoxy)-6-(((2<i>S</i>,3<i>S</i>,4<i>S</i>,5<i>R</i>,6<i>R</i>)-3-acetoxy-4,5-bis(benzyloxy)-6-((benzyloxy)methyl)tetrahydro-2<i>H</i>-pyran-2-yl)oxy)methyl)tetrahydro-2<i>H</i>-pyran-3,4,5-triyl tribenzoate (CAS RN 12334475-58-5), - 35 % or more but not more than and 45 % of tolu-ene (CAS RN 108-88-3) | S | New | UNDER EXAMINATION | FR | Applicant | Round 2025/7 - API to be used in pharmaceutical product for genetic hereditary diseases |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|--|
| 3824 99 96 | | 6704901/2024 | 3353 | Preparation containing by weight: - 30 % or more, but not more than 60 % of 3a,4,4a,5,8,8a,9,9a-octahydro-1H-4,9:5,8-dimethanocyclopenta[b]naphthalene (CAS RN 7158-25-0), - 10 % or more, but not more than 50 % of 3a,4,7,7a-tetrahydro-4,7-methanoindene (CAS RN 77-73-6) and - whether or not 10 % or more, but not more than 40 % of petroleum hydrocarbon resin (CAS RN 68132-00-3) | S | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 used as coating for liners and pipes and in the production of composite parts |
| 3824 99 96 | | 6542127/2024 | 1031 | Vulcanizing material containing by weight of - 78% or more but not more than 82 % insoluble sulphur (CAS RN 9035-99-8), - 18% or more but not more than 22 % naphthenic oil (CAS RN 64742-52-5), and - less than 0,2 % methyl styrene (CAS RN 98-83-9) | S | New | UNDER EXAMINATION | TR | Applicant | Round 2025/7 Used as an anti-revision agent for natural rubber and isoprene rubber |
| 3824 99 96 | | 6704973/2024 | 3354 | Preparation containing by weight: - 80 % or more, but not more than 90 % of 3a,4,7,7a-tetrahydro-4,7-methanoindene (CAS RN 77-73-6), and - Whether or not but not more than 10 % of 3a,4,4a,5,8,8a,9,9a-octahydro-1H-4,9:5,8-dimethanocyclopenta[b]naphthalene (CAS RN 7158-25-0), and - 0,5 % or more, but not more than 3 % of 2,6-di-tert-butyl-p-cresol (CAS RN 128-37-0) | S | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 for use in the production of composite parts, structural components, rebars and automotive panels |
| 3824 99 96 | | 6675420/2024 | 3338 | Butyl methacrylate (CAS RN 97-88-1) of a purity by weight of 99 % or more and methyl methacrylate (CAS RN 80-62-6) of a purity by weight of more than 0,1 % but not more than 0,5 % | S | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 used in the production of acrylic resins |
| 3824 99 96 | | 6542168/2024 | 1032 | Vulcanizing material containing by weight - 20 % naphthenic oil (CAS RN 64742-52-5), - 80 % insoluble sulfur containing (CAS RN 9035-99-8) | S | New | UNDER EXAMINATION | TR | Applicant | Round 2025/7 Used as a revision inhibitor agent for natural rubber and isoprene rubber |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|---|
| 3906 90 90 | | 6548275/2024 | 3304 | Acrylonitrile styrene acrylate copolymer in the form of granules containing: <ul style="list-style-type: none"> - 48 % styrene, - 22 % acrylonitrile, - 29 % butylacrylate, and - 1 % dihydrodicyclopentadienyl acrylate | S | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 base material for the production of plastic components |
| 3907 29 20 | | 7015635/2024 | 1043 | Glycerol (CAS RN 31694-55-0), ethoxylated based polyol with a hydroxyl number of 541 or more but not more than 587 | S | New | UNDER EXAMINATION | TR | Applicant | Round 2025/7 used for Polyurethane Foam |
| 3907 29 20 | | 6536442/2024 | 1029 | Poly[oxy(methyl-1,2-ethanediyl)], α -hydro- ω -hydroxy-, ether with b-D-fructofuranosyl a-Dglucopyranoside (CAS RN 9049-71-2) | S | New | UNDER EXAMINATION | TR | Applicant | Round 2025/7 used to produce conventional rigid foams |
| 3907 29 99 | | 6704740/2024 | 3351 | Polyethylene glycol with an ethylene oxide chain length of not more than 30, having butyl-2-cyano 3-(4-hydroxyphenyl) acrylate end groups (CAS RN 780763-40-8) | S | New | UNDER EXAMINATION | BE | Applicant | Round 2025/7 |
| 3911 10 00 | | 6542237/2024 | 3300 | Combination of organic compounds, predominantly 100 % hydrocarbons, obtained as a fraction of the extract from solvent extraction of the residue | S | New | UNDER EXAMINATION | TR | Applicant | Round 2025.7 - homogenizing agent for different elastomers to be used in radial automobile tire |
| 3911 10 00 | | 6542308/2024 | 3301 | Petroleum resin containing by weight <ul style="list-style-type: none"> - more than 98 % asphalt (CAS RN 8052-42-4), - less than 2 % Hydrated Amorphous Silica (CAS RN 112926-00-8) | S | New | UNDER EXAMINATION | TR | Applicant | Round 2025/7 homogenizing agent for elastomers to be used in radial automobile tire |
| 3920 30 00 | | 6633644/2024 | 3323 | Biaxially oriented, non-cellular high impact polystyrene (HIPS) foil in rolls whether or not printed with: <ul style="list-style-type: none"> - a thickness of 0,229 mm or more but not more than 0,279 mm, - an opaque with titanium dioxide content of 3 % or more but not more than 3.5 %, | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025/7 - used for production of a medial device |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|---|
| | | | | <ul style="list-style-type: none"> - a width of 82,05 mm or more but no more than 83,05 or 107,45 or more but no more than 108,45 mm, - a water mobility of 20 degrees or more but not more than 23 degrees, - a reflectance of 57 % or more, - a waviness of not more than 1 mm out of flatness, - a super hydrophobic coating chemically neutral and non-reactive to other substances, especially to chemical reagents intended for urine diagnostics | | | | | | |
| 3920 62 19 | | 6569498/2024 | 3314 | <p>Three-layer plastic film consisting of a 15 µm fluorinated polymer (FCC) (EVA) layer, a 275 µm polyethylene terephthalate (PET) layer and a 25 µm fluorinated polymer (FCC) layer:</p> <ul style="list-style-type: none"> - with a total thickness of 300-330 µm, - with a tensile strength of ≥ 375 N/cm in both the longitudinal and transverse directions (ASTM D-882), - with a low thermal shrinkage of ≤ 1,0 % at 150 °C for 30 minutes, - a low water vapour permeability of ≤ 2,5 g/m²²•d, and - with a high breakdown voltage ≥18 kV and a partial discharge voltage ≥1500 VDC (BG/T 123542.2-2009) <p>to be used as a protective layer on the back of photovoltaic modules, to provide insulation and protection against external influences.</p> | S | New | UNDER EXAMINATION | SI | Applicant | Round 2025/7 - used as protective layer for solar modules |
| 3920 99 21 | | 6536343/2024 | 1028 | <p>Polyamide film with a length of 100 µm or more but not more than 200 µm</p> | S | New | UNDER EXAMINATION | TR | Applicant | Round 2025/7 used in the production of manufacturer production labels |
| 7007 19 80 | | 6663234/2024 | 3335 | <p>A tempered glass in a circular shape with:</p> <ul style="list-style-type: none"> - a light transmittance of 34,2 % or more but not more than 37,8 %, | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025/7 for use in the cover of door |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|---|
| | | | | <ul style="list-style-type: none"> - a diameter of 477,2 mm or more but not more than 477,8 mm, - a thickness of 2,9 mm or more but not more than 3,5 mm, - a weight of 1345 g or more but not more than 1445 g, - 3-zone structure including Euro Deep Gray colour printed zone, <p>for the cover of door assembly in washing machines (1)</p> | | | | | | assembly in washing machines |
| 7019 80 10 | | 6663116/2024 | 3333 | <p>A vacuum insulation panel consisting of a gas-tight housing surrounding a rigid core devoid of air:</p> <ul style="list-style-type: none"> - with fiberglass or chopped fiberglass filling, - a thickness of 5,6 mm or more but not more than 20,4 mm, - a length of 195 mm or more but not more than 1 835 mm, - a width of 155 mm or more but not more than 545 mm, - a thermal conductivity lower than 2,5 mW/mK, - an internal pressure of 0,1 Pa, - ambient temperature during operation of - 50 °C or more but not more than 70 °C | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025/7 used for production of refrigerators, freezers and fridge-freezers |
| 7606 91 00 | | 6633432/2024 | 3318 | <p>Aluminium cutout of a rounded shape made from non-alloy aluminium AA 1050:</p> <ul style="list-style-type: none"> - laminated with a layer of fleece or hot-melt adhesive, - with a total thickness of 0.9 mm or more, but not more than 1.1 mm, - with an aluminum layer thickness of 0.8 mm or more, but not more than 0.9 mm, - embossed with a geometric pattern - lacquered and coated with a protective layer | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025/7 - for use in interior details of passenger cars |
| 8406 81 00 | | 6501845/2024 | 1023 | <p>Industrial steam turbine with:</p> <ul style="list-style-type: none"> - an output of 40 MW or more but not more than 60 MW, | S | New | UNDER EXAMINATION | DE | Applicant | Round 2025/7 used for the production of power generation units |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|--|
| | | | | <ul style="list-style-type: none"> - designed for a pressure of not more than 140 bar and a temperature of not more than 540 ° C, - equipped with double seat valves on the live steam side which are operated with a hydraulic servo of not more than 30 bar | | | | | | |
| 8409 99 00 | | 2556095/2024 | 1512 | <p>Die cast aluminium housing for electronic throttle control or exhaust gas recirculation systems:</p> <ul style="list-style-type: none"> - high pressure-casted of EN AC-46000 aluminium, - shot-blasted and machined, - with a height of 100 mm or more but not more than 135 mm, - with a width of 115 mm or more but not more than 150 mm, - with a weight of 210 g or more but not more than 465 g | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025-07 roll over Round 2025/1 Used in car production |
| 8412 21 80 | | 6633775/2024 | 3325 | <p>Hydraulic actuators of a kind used in the arms of machines for handling cargo containers:</p> <ul style="list-style-type: none"> - with a weight of 827 kg or more but not more than 935 kg, - with a diameter of 250 mm or more but not more than 330 mm, - with a length of 3480 mm or more but not more than 4115 mm, - with a stroke of 2750 mm or more but not more than 3180 mm, - adapted to work with hydraulic oil at a working pressure of 23 MPa, - whether or not with a maintenance-free bearing without the need for lubrication | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025/7 - to be used in in the moveable hydraulic arm of reach stacker machines |
| 8412 21 80 | | 6662606/2024 | 3326 | <p>Hydraulic actuators of a kind used in the machines for handling cargo containers:</p> <ul style="list-style-type: none"> - with a weight of 45 kg or more but not more than 57 kg, - with a diameter of 119 mm or more but not more than 149 mm, - with a length of 779 mm or more but not more than 1141 mm, | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025/7 - used in machines for handling cargo containers |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|--|
| | | | | <ul style="list-style-type: none"> - with a stroke of 450 mm or more but not more than 610 mm, - adapted to work with hydraulic oil at a working pressure of 22 MPa or more but not more than 23 Mpa, - whether or not with a maintenance-free bearing without the need for lubrication | | | | | | |
| 8414 30 20 | | 6662813/2024 | 3329 | <p>Hermetic refrigeration compressor for R-600a as refrigerant:</p> <ul style="list-style-type: none"> - not charged with refrigerant, - pre-charged with the lubricant oil with oil charge 150 cm3 or higher, but not higher than 170 cm3, - with a brushless DC electric motor (BLDC), - having right side suction connection with inner diameter of 6,44 mm or more, but not more than 6,64 mm and right side discharge connection of inner diameter 4,85 mm or more, but not more than 5,05 mm, - with displacement 9,93 cm3 or higher, but not higher than 10,13 cm3, - running at 1 300 rpm or faster, but not faster than 4 500 rpm, - with a cooling capacity of 80 W or higher, but not higher than 273 W | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025/7 - for use in refrigeration systems |
| 8414 30 89 | | 7128266/2024 | 1046 | <p>Compressor for motor vehicle air conditioning system:</p> <ul style="list-style-type: none"> - electrical compressor with a power output of more than 0,4 kW but not exceeding 10 kW for use in the manufacture of motor vehicles under Chapter 87 (1) | S | New | UNDER EXAMINATION | TR | Applicant | Round 7/25 For use in the manufacture of motor vehicles |
| 8418 99 90 | | 6662970/2024 | 3331 | <p>An evaporator being a type of heat exchanger, consisting of aluminium pipes with copper ends enclosed with aluminium radiators:</p> <ul style="list-style-type: none"> - measuring 403 x 276 x 70 mm or more, but not more than 464 x 399 x 83 mm, - with a total weight of a set of 236 g or more, but not more than 1 010 g, - with a fixed sensor, | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025/7 for use in the manufacture of freezers or refrigerators |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|---|
| | | | | <ul style="list-style-type: none"> - with noise absorber, - with 2, 5 or 7 control and power connection pins terminated with sensor temperature, heater or fuse type of socket <p>for use in the manufacture of freezers or refrigerators (1)</p> | | | | | | |
| 8431 20 00 | | 6662678/2024 | 3327 | <p>Concrete counterweights of a kind used in machines for handling transport containers and forklifts with:</p> <ul style="list-style-type: none"> - a weight of 2 100 kg or more but not more than 13 000 kg, - a height of 30 cm or more but not more than 110 cm, - a length of 160 cm or more but not more than 260 cm, - a width of 195 cm or more but not more than 330 cm, - smoothed edges, - colored pain coated, - whether or not encased steel sheet with a thickness of 5 mm or more | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025/7 - to be used in specialized machines for handling heavy loads |
| 8431 20 00 | | 6662758/2024 | 3328 | <p>Container spreader of a kind used for lifting empty 20' and 40' cargo containers:</p> <ul style="list-style-type: none"> - without an integrated carriage, - suitable for machines with a load capacity of not more than 11 000 kg, - designed to carry one or two containers at a time, - with a top or side mounting, - with an anti-corrosion layer coated, - with a weight of 3 200 kg or more but not more than 4 000 kg | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025/7 - used for production of specialized machines for handling heavy loads |
| 8481 80 59 | | 6501431/2024 | 1019 | <p>Solenoid valve of combustion engine oil pump for regulating the amount of oil in the pump:</p> <ul style="list-style-type: none"> - with cable with length of 550 mm or more but not more than 700 mm with electrical connector - with an operating pressure of not more than 5.5 bar, | S | New | UNDER EXAMINATION | SK | Applicant | Round 2025/7 for use in the manufacture of engines of motor vehicles |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|--|
| | | | | <ul style="list-style-type: none"> - with an operating voltage of 9 VDC or more but not more than 16 VDC, - with a valve's base width of 22 mm but not more than 27 mm, - with a valve's length of 55 mm but not more than 110 mm, <p>for use in the manufacture of engines of motor vehicles (1)</p> | | | | | | |
| 8483 10 95 | | 6663039/2024 | 3332 | <p>Assy shaft of DRUM for torque transmission, made of steel (per SM45C for shaft standard and STS430 for ring standard) with:</p> <ul style="list-style-type: none"> - a length of 137,8 mm or more but not more than 138,2 mm - an outer diameter of 23 mm or more but not more than 48,025 mm, - a weight of 1,0245 kg or more but not more than 1,0445 kg, - a hardness of shaft 40 HRC or more but not more than 50 HRC, - a hardness of ring 90 HRB or more, but no more than 120 HRB, - an external 37-teeth spline with major diameter of 41 mm or more but not more than 48 mm | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025/7 |
| 8501 31 00 | | 6633590/2024 | 3322 | <p>Electric brushless direct current motor finished with biocompatible materials such as stainless steel according to specification 17-4 PH or type 303, 316L, 400 with:</p> <ul style="list-style-type: none"> - a three-phase winding, - an output power not exceeding 280 W, - a length with gearhead of 116,1 mm or more but not more than 117,2 mm, - an external diameter of 13,86 mm or more but no more than 13,92 mm, - a maximum torque of motor with gearhead 246,6 mNm in 25°C, - a no-load radial speed of motor with gearhead at 24 V-25°C 9 900 rpm, - a weight of motor with gearhead of 70,5 g or more but not more than 71,5 g, | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025/7 - for use in the manufacture of medical devices |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|--|
| | | | | <ul style="list-style-type: none"> - a resistance to peak temperature of 140°C or more (non-operating), - a maximal air leak between shaft and shaft seals of 15 Pa/s at given 2 Bars of pressure, - 14 functional pins for power and control purpose, - a flexible printed circuit with length of 245 mm but no longer than 255 mm with mounted 8 pin male connector <p>for use in the manufacture of medical devices with right-left rotation and oscillation function (1)</p> | | | | | | |
| 8501 31 00 | | 6662876/2024 | 3330 | <p>Brushless DC electric motor, with:</p> <ul style="list-style-type: none"> - a rated voltage DC310V PWM Voltage, - a rated power of 350 W or more but not more than 368 W, - an input power of 500 W or more but not more than 550 W, - output power of 350 W or more but not more than 400 W, - an external diameter without bracket connector and pulley of 143,2 mm or more but not more than 143,8 mm, - a rated speed of 16300 rpm or more but not more than 16500 rpm, - a weight of 2,33 kg or more but not more than 2,40 kg, - a pulley | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025/7 - to be used in the manufacture of washing machines |
| 8501 51 00 | | 6633467/2024 | 3319 | <p>Electric permanent magnet synchronous motor with:</p> <ul style="list-style-type: none"> - an output power of 550 W, - a rotor containing 8 poles generated by permanent magnets made with a composition of neodymium-iron-boron (per GB/T 13560 standard) enclosed in polyethylene cover, - an outer diameter of motor magnet shaft end with dimension of 10,001 mm or more but no more than 10,007 mm, - terminals located across the radius 32,5 mm and separated by an angle of 21,8°, - a motor housing made of ADC12 or AC46000 aluminium alloy die casting with | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025/7 - for use as part of the electric power steering system of cars |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|---|
| | | | | <p>composition of aluminium-silicon-copper (per JIS H5302 or EN1706 standard),</p> <ul style="list-style-type: none"> - a back EMF constant (Ke) of 0,03306 V-sec/rad or more but no more than 0,03654 V-sec/rad, - a back EMF harmonics order - 5th of no more than 0,38 % (of fundamental) and 7th of no more than 0,25 % (of fundamental), - a cogging torque of no more than 13 mNm, - a friction torque in ambient temperature of no more than 22 mNm, - a maximum temperature of motor operation not more than 200 °C | | | | | | |
| 8501 51 00 | | 6633489/2024 | 3320 | <p>Electric permanent magnet synchronous motor with:</p> <ul style="list-style-type: none"> - an output power of 600 W, - a rotor containing 8 poles generated by permanent magnets made of composition of iron, neodymium, boron and dysprosium enclosed in aluminium cover, - an outer diameter of motor magnet shaft end with dimension of 10,001 mm or more but no more than 10,007 mm, - terminals located across the diameter 59,2 mm and separated by an angle 30,0°, - a housing made of electrogalvanized steel (per JIS G3313 Grade SECE standard) using a deep-drawing stamping process, - a diameter of 88,600 mm or less but no less than 88,546 mm at the motor-system assembly interface, - a back EMF constant (Ke) of 0,03277 V-sec/rad or more but no more than 0,03623 V-sec/rad, - • a back EMF harmonics order - 5th of no more than 0,35 % (of fundamental) and 7th of no more than 0,30 % (of fundamental), - a cogging torque of no more than 12 mNm, - a friction torque in ambient temperature of no more than 23 mNm, - a maximum temperature of motor operation not more than 200 °C | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025/7 - used as part of the electric power steering system of cars |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|---|
| 8501 52 20 | | 6633548/2024 | 3321 | <p>Electric permanent magnet synchronous motor with:</p> <ul style="list-style-type: none"> - an output power of 850 W, - a rotor containing 8 poles generated by permanent magnets made with a composition of neodymium-iron-boron (per GB/T 13560 standard) enclosed in polyethylene cover, - an outer diameter of motor magnet shaft end with dimension of 10,001 mm or more but no more than 10,007 mm, - terminals located across the radius 26,2 mm and separated by an angle 30,0°, - a housing made of ADC12 or AC46000 aluminium alloy die casting with composition of aluminium-silicon-copper (per JIS H5302 or EN1706 standard) and anodized coating (per ASTM B580 type E standard), - a back EMF constant (Ke) of 0,04009 V-sec/rad or more but no more than 0,04431 V-sec/rad, - a back EMF harmonics order - 5th of no more than 0,36 % (of fundamental) and 7th of no more than 0,24 % (of fundamental), - a cogging torque of no more than 20 mNm, - a friction torque in ambient temperature of no more than 26,5 mNm, - a maximum temperature of motor operation not more than 200 °C | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025/7 - used as part of the electric power steering system of cars |
| 8503 00 99 | | 2556164/2024 | 1666 | <p>Pressure casted rotor front plate or cover of an electric supercharger:</p> <ul style="list-style-type: none"> - of EN AC-46000 aluminium, - shot-blasted and machined, - with an HBW of 60 or more (2,5/62,5, according to ISO 6506), - with a tensile strength of 240 N/mm² or more, - with a height of 22 mm or more but not more than 26 mm, - with a diameter of 128 mm or more but not more than 136 mm, - with a weight of 220 g or more but not more than 250 g | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025-07 roll over Round 2025/1 used for engine production |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|---|
| 8505 11 10 | | 2544759/2024 | 1500 | <p>Magnetized upper rotor made with steel stack according to standards ASTM A677-07 grade 47F180 or JIS C 2552 Grade 50A310, with:</p> <ul style="list-style-type: none"> - twelve permanent magnets made with neodymium-iron-boron, enclosed in stamped steel stack ring, - a residual induction value 1,21 T or more but not more than 1,32 T. at 25° C, - an inner diameter of 22,735 mm or more but no more than 22,835 mm, - an outer diameter of 30,725 mm or more but no more than 38,025 mm <p>for use in the manufacture of vehicle's steering system (1)</p> | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025/7 Roll over Round 2025/1 for use in car production - rejected |
| 8507 60 00 | | 7128403/2024 | 1048 | <p>Modules used for the assembly of lithium-ion electric accumulators:</p> <ul style="list-style-type: none"> - contains 12 or more cells but not more than 36 cells, - with a nominal capacity of 51 Ah per cell, - with a nominal voltage of 60 V or more, but not more than 120 V, - with a weight of 18 kg or more but not more than 36 kg, - with a width of 100 mm or more but no more than 220 mm, - with a height of 80 mm or more but no more than 180 mm, - with a length of 700 mm or more but no more than 1 200 mm, <p>for use in the manufacture of motor vehicles of subheading 8703.60 (1)</p> | S | New | UNDER EXAMINATION | TR | Applicant | Round 2025/7 for use in the manufacture of motor vehicles of subheading 8703.60 |
| 8507 60 00 | | 7128192/2024 | 1045 | <p>Rechargeable lithium-ion battery pack:</p> <ul style="list-style-type: none"> - with a length of 1 050 mm or more but not exceeding 1 070 mm, - with a width of 624 mm or more but not exceeding 636 mm, - with a height of 235 mm or more but not exceeding 255 mm, | S | New | UNDER EXAMINATION | TR | Applicant | Round 7/25 For use in the manufacturing of electric buses |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|--|
| | | | | <ul style="list-style-type: none"> - with a weight of 210 kg or more but not exceeding 230 kg, - with a nominal capacity of 215 Ah or more but not exceeding 315 Ah, - with power not exceeding 45 kWh, - with a nominal voltage of 100 V or more but not exceeding 175 V, - with a capacity not exceeding 400 Ah | | | | | | |
| 8507 60 00 | | 7128336/2024 | 1047 | <p>Lithium ion battery:</p> <ul style="list-style-type: none"> - contains 48 or more cells but not more than 84 cells - consists of 2 or more modules but not more than 4 modules - with a nominal capacity of 4,08 Ah per cell - with a nominal voltage of 200 V or more, but not more than 426 V - with a weight of 9 kg or more but not more than 48 kg - with a width of 280 mm or more but no more than 360 mm, - with a height of 150 mm or more but no more than 220 mm, - with a length of 600 mm or more but no more than 1 200 mm, <p>for use in the manufacture of motor vehicles of Chapter 87 (1)</p> | S | New | UNDER EXAMINATION | TR | Applicant | Round 7/25 for use in the manufacture of motor vehicles |
| 8537 10 91 | | 6633310/2024 | 3316 | <p>Electronic assembly containing:</p> <ul style="list-style-type: none"> - a microprocessor, - a programmable memory and other electronic components mounted on a printed circuit, - with or without light-emitting diode (LED) or Thin Film Transistor (TFT) or Liquid Crystal Display (LCD technology) indicators <p>for use in the manufacture of products of subheadings 7321 11, 8414 60, 8418 10, 8418 21, 8418 29, 8418 40, 8421 12, 8422 11, 8450 11, 8450 12, 8450 20, 8450 19, 8451 21, 8451 29 and 8516 60</p> | S | New | UNDER EXAMINATION | HU | Applicant | Round 2025.7 - control circuit boards for household appliances |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|--|
| | | | | (1) | | | | | | |
| 8544 30 00 | | 6633735/2024 | 3324 | <p>The wire harness ensures the board communication with the other components of the car's EPS (Electrical Power Steering) system with:</p> <ul style="list-style-type: none"> - a length of 170 mm or more but not more than 301 mm, - an outer diameter of 4,5 mm or more but not more than 5,20 mm, - an operating temperature of - 40°C or more but not more than 125°C, - exposed wire end with a maximum diameter of 0,8 mm after tinning, - connectors, - a gold or tin plating terminals, - an XL-PE or TPE-E wire insulation material | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025/7 - for use in the electrical power steering system of cars |
| 8544 42 90 | | 6663164/2024 | 3334 | <p>Wire harness with a 26-PIN or 28-PIN wire to board connectors in crimping technology for the transmission of signals and/or electrical power bound by rubber or vinyl or electrical tape or conduit or a weave of extruded string or a combination of thereof for connection of power supply with main printed (circuit) board assembly (PBA) and electrical components of refrigerator or washing machine (1)</p> | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025/7 used for production of refrigerators and washing machines |
| 8708 40 20 | | 6502232/2024 | 1025 | <p>Transmission assembly consisting of:</p> <ul style="list-style-type: none"> - double pinion type planetary gear shifting mechanism, - sport sequential shiftmatic system that does not have lower than 7-speed and not higher than 10-speed - with the dimensions of: - a width of 280 mm or more but no more than 470 mm, - a height of 350 mm or more but no more than 595 mm, - a length of 410 mm or more but no more than 690 mm, | S | New | UNDER EXAMINATION | TR | Applicant | Round 2025/7 For use in the manufacture of motor vehicles of Chapter 87. |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|--|
| | | | | <ul style="list-style-type: none"> - a weight of 70 kg or more but no more than 110 kg, for use in the manufacture of motor vehicles of Chapter 87 (1) | | | | | | |
| 8708 40 50 | | 6502103/2024 | 1024 | Transmission assembly which houses 3 other shafts inside it and offers a rotating switch for shift position, consisting of: <ul style="list-style-type: none"> - cast aluminum body, - differential gear, - 2 electrical machines and gears - with the dimensions of: - a width of 280 mm or more but no more than 470 mm, - a height of 350 mm or more but no more than 595 mm, - a length of 410 mm or more but no more than 690 mm, for use in the manufacture of motor vehicles of Chapter 87 (1) | S | New | UNDER EXAMINATION | TR | Applicant | Round 2025/7 For use in the manufacture of motor vehicles of Chapter 87. |
| 8708 91 35 | | 6469652/2024 | 1017 | Radiators with corrosion protection, for pressures up to 150 PSI (1034 kPa) with individual replaceable, cooling tubes in brass or copper for use in the production of engine and charge air cooling with a weight of 265 kg or more but not more than 599 kg | S | New | UNDER EXAMINATION | SE | Applicant | Round 2025/7 integrated into the powertrain system during the manufacturing of mining trucks |
| 8708 94 99 | | 2555819/2024 | 1508 | Torsion bar as part of the steering column made of carbon alloy steel (per SAE J1268, grade 5160H of modified chemistry for carbon content of 0,53 or more, but not more than 0,56) with: <ul style="list-style-type: none"> - a shaft torsional stiffness of 2,5 Nm/degree or more but not more than 2,7 Nm/degree, - a length of 107,75 mm or more but no more than 108,25 mm, - an outer diameter of 6,38 mm or more but no more than 6,42 mm, - two external 18-tooth splines on both shaft ends with a major diameter of 6,70 mm or more but | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025-07 roll over Round 2025/1 used in car production |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|--|
| | | | | <ul style="list-style-type: none"> - no more than 6,85 mm, as interface to pressing with matting input and output shafts, - entire surface shot peened for use in the manufacture of vehicle's steering system (1) | | | | | | |
| 8708 94 99 | | 2544451/2024 | 1501 | Outer tie rod with a housing made of AISI 4137 (SCM435) steel or EN10083/2- C45R + N steel or JIS G4053-SCM435 low alloy steel, with: <ul style="list-style-type: none"> - a ball stud made of EN 10263/4 – 41CrS4 Q + T steel or AISI 4137 (SCM435) steel or - EN10083/3-42CrMoS4Q + T steel or JIS G4053-SCM435 low alloy steel, - a ball seat made of polyoxymethylene plastic, - an end of the threaded hole to the ball stud center distance of 124 mm or more but no more than 194 mm, - a ball stud diameter of 21,98 mm or more but no more than 22 mm, - a threaded hole depth of 40,5 mm or more but no more than 52 mm with dimensions M14x1,5, - a boot seal, - a boot seal protector and retaining ring, - lubricant, for use in the in manufacture of vehicle's steering system (1) | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025-07 - roll over Round 2025/1 components for the automotive industry |
| 8708 94 99 | | 2545142/2024 | 1502 | Hub gear made of cold rolled carbon steel (per ASTM A1008), molded into the plastic and pressed on pinion, with: <ul style="list-style-type: none"> - an outer diameter of 81,2 mm or more, but not more than 82,55 mm, - an inner diameter of 25,9 mm or more, but not more than 25,97 mm, - a height of the lower side of inner diameter of 11,63 mm or more, but not more than 12,13 mm, - a height of the upper side of inner diameter of 3,25 mm or more, but not more than 3,5 mm, | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025-07 - Roll over. Round 2025/1 used in car production |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----------|----------------------|---|
| | | | | <ul style="list-style-type: none"> - an overall height of 11,63 mm or more, but not more than 19,5 mm for use in the manufacture of vehicle's steering system (1) | | | | | | |
| 8708 94 99 | | 2550880/2024 | 1503 | Shaft intermediate steering assembly as part of the steering column with: <ul style="list-style-type: none"> - a torsional stiffness of 25 Nm/degree or more, - a shaft assembly male tubular made of carbon steel welded tube (per GB/T 699 grade 20), - a shaft assembly female tubular made of carbon steel welded tube (per GB/T 699 grade 20), - two spiders universal joint made of chromium alloy steel (per GB/T 5216 grade 20CrMnTiH), - a length in nominal telescope position of 396 mm or more but not more than 467 mm, - a coupling interface on both ends with internal toothing, - two cardan joints on both sides, - a telescope shaft function with a range of 74 mm or more but not more than 115 mm, for use in the manufacture of vehicle's steering system (1) | S | New | UNDER EXAMINATION | PL EU | Applicant Opposed | Round 2025-07 roll over. Round 2025/1 components for the automotive industry |
| 8708 94 99 | | 2550954/2024 | 1504 | Lower assist shaft as part of the steering column made of carbon steel (per GB/T699 grade 45 or JIS G4051 grade S45C) with: <ul style="list-style-type: none"> - an ultimate torsional strength load of 325 Nm or more and J.A.E.L values of 275 Nm or more, - a length of 66,39 mm or more but not more than 88,64 mm, - an outer diameter of 27,47 mm or more but not more than 28,38 mm, - an inner hole of diameter 6,50 mm or more but not more than 6,58 mm, - an external 26-teeth spline with major diameter 21,18 mm or more but not more than 21,44 mm, | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025-07 - roll over. Round 2025/1 used in car production |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|--|
| | | | | <ul style="list-style-type: none"> - a knurling on a part of outer surface of major diameter 26,0 mm or more but not more than 26,1 mm, - with or without an external 24-tooth spline and with a major diameter 24,75 mm or more but not more than 25 mm, <p>for use in the manufacture of vehicle's steering syste (1)</p> | | | | | | |
| 8708 94 99 | | 2551185/2024 | 1507 | <p>Tubular steering shaft as part of the steering column made of carbon steel welded tube (per EN 10305/2, E235 + C or GB/T699 grade 20) with:</p> <ul style="list-style-type: none"> - an ultimate torsional strength of 300 Nm or more and J.A.E.L values of 275 Nm or more, - a length of 245,48 mm or more but not more than 287,5 mm, - an outer diameter of 23,95 mm or more but not more than 32,25 mm, - an interface for steering wheel connection either in a form of an external 40-tooth spline with major diameter of 17,1 mm or more but not more than 17,5 mm and an internal thread - M12x1,75-6H or in a form of an external hexagon with a short diagonal of 15,05 mm or more but not more than 15,35mm and an internal thread M10x1.5-6H, - an interface either in a form of an internal 10-tooth spline of length of 98 mm or more but not more than 160 mm, with minor diameter of 16,1 mm or more but not more than 16,4 or in a form of an internal 48-tooth spline of length of 151 mm or more but not more than 160 mm, with minor diameter of 23,2 mm or more but not more than 23,3 mm, <p>for use in the manufacture of vehicle's steering system (1)</p> | S | New | UNDER EXAMINATION | PL | Applicant | <p>Round 2025-07 - roll over. Round 2025/1 used for car production</p> |
| 8708 94 99 | | 2551124/2024 | 1506 | <p>Lower shaft as part of the steering column made of aluminum alloy (per ASTM B221M grade 6105), air quenched and tempered with:</p> <ul style="list-style-type: none"> - an ultimate torsional strength of 260 Nm or more, | S | New | UNDER EXAMINATION | PL | Applicant | <p>Round 2025-07 - roll over Round 2025/1 components for automotive industry</p> |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|---|
| | | | | <ul style="list-style-type: none"> - a length of 296,7 mm or more but not more than 297,8 mm, - an external 18-tooth spline on all shaft length with major diameter of 28,7 mm or more but not - more than 29 mm, - an 18-tooth internal spline with a minor diameter of 19,7 mm or more but not more than 20 mm, <p>for use in the manufacture of vehicle's steering system (1)</p> | | | | | | |
| 8708 94 99 | | 2551037/2024 | 1505 | <p>Upper assist shaft as part of the steering column made of carbon steel (per GB/T699 grade 45) with:</p> <ul style="list-style-type: none"> - an ultimate torsional strength load of 325 Nm or more and J.A.E.L values of 275 Nm or more, - a length of 165,3 mm or more but not more than 204,2 mm, - an outer diameter of 22,87 mm or more but not more than 22,92 mm, - an internal hole of diameter 6,50 or more but not more than 6,58 mm, - an external spline, <p>for use in the manufacture of vehicle's steering system (1)</p> | S | New | UNDER EXAMINATION | PL | Applicant | Round 2025-07 - roll over Round 2025/1 used for car production |
| 9503 00 75 | | 2558847/2024 | 1509 | <p>Miniature engine:</p> <ul style="list-style-type: none"> - consisting of a plastic body, - with shaft length 11 cm or more but not more than 15,5 cm, - allowing the gears to rotate by means of the cables it contains transmitting electric current, <p>for use in the manufacture of the toys under heading 9503 (1)</p> | S | New | UNDER EXAMINATION | TR | Applicant | Round 2025-07 - roll over. Round 2025/1 use in the manufacture of the toys |
| 9503 00 75 | | 2558894/2024 | 1510 | <p>Miniature engine:</p> <ul style="list-style-type: none"> - consisting of a metal body, - allowing the gears to rotate by means of the cables transmitting electric current, | S | New | UNDER EXAMINATION | TR | Applicant | Round 2025-07 roll over Round 2025/1 use in the manufacture of the toys |

| | | | | | | | | | | |
|---------------|----|------------------------|------|--|---|------------------|-------------------|----------|---------------------------|---|
| | | | | for use in the manufacture of the toys under heading 9503 (1) | | | | | | |
| ex 2841 80 00 | 20 | 2656815/2022 | 5039 | AT (13.09.2024): Disodium tungstate (CAS RN 13472-45-2) with a purity by weight of 75 % or more --- Current description: Disodium tungstate (CAS RN 13472-45-2) with a: - purity by weight of 99 % or more, - chlorine content of less than 100 ppm | S | Amendment | UNDER EXAMINATION | AT | Applicant | Round 2025-07 request for amendment.// Round 2023/1 used to manufacture tools, parts for the automotive, aircraft, medicine techn. industry |
| ex 2850 00 20 | 80 | 1997/1/2001 | 5002 | Arsine (CAS RN 7784-42-1) with a purity by volume of 99,999 % or more | S | Amendment | UNDER EXAMINATION | BE | Applicant | Round 2025-07 request for amendment. To consider adding the use of the product. |
| ex 2907 29 00 | 85 | 2514/1/04 3112/1/04 | 5012 | FR(10.09.2024): Phloroglucinol anhydre (CAS RN 108-73-6) or phloroglucinol dihydrate (CAS RN 6099-90-7) with a purity by weight of 95 % or more --- Current product description: Phloroglucinol whether or not hydrated | S | Amendment | UNDER EXAMINATION | NL FR | Applicant Co-applicant | Round 2025-07 request for amendment.// |
| ex 2909 19 90 | 30 | 1914/2/2003 | 5003 | DG ENV: Reaction mass of 1,1,2,3,3,3-hexafluoro-1-methoxy-2-(trifluoromethyl)propane and 1,1,2,2,3,3,4,4,4-nonafluoro-1-methoxybutane --- Current text: Mixture of isomers of nonafluorobutyl methyl ether or nonafluorobutyl ethyl ether, of a purity by weight of 99 % or more | S | Amendment | UNDER EXAMINATION | BE | Applicant | Round 2025-07 - request for amendmnet. |

| | | | | | | | | | | |
|---------------|----|-------------|-------|--|---|-----------|-------------------|----------------|--------------------------------------|--|
| ex 2909 60 90 | 10 | 2452/2/04 | 5057E | Bis(α,α -dimethylbenzyl) peroxide (CAS RN 80-43-3) | S | Amendment | UNDER EXAMINATION | DE BE EU | Applicant Co-applicant Opposed | Round 2025-07 Objection. ECHA has recently communicated that the following substance has been identified as SVHC. |
| ex 2914 29 00 | 40 | 1687/3/1996 | 5013 | FR(03.09.2024): Bornan-2-one (CAS 76-22-2) with a with a purity by weight of 90 % or more --- Current product description: Camphor (CAS 76-22-2) | S | Amendment | UNDER EXAMINATION | FR | Applicant | Round 2025-07 request for amendment.// |
| ex 2915 39 00 | 85 | 288754/2013 | 5040 | FR(13.09.2024): cis 2- tert-butylcyclohexyl acetate (CAS RN 20298-69-5) --- Current description: 2-tert-Butylcyclohexyl acetate (CAS RN 88-41-5) | S | Amendment | UNDER EXAMINATION | IT | Applicant | Round 2025-07 request for amendment. used in the manufacture of detergents, cosmetics and perfumes |
| ex 2918 99 90 | 70 | 249933/2009 | 5014 | NL(28.08.2024): Allyl-(3-methylbutoxy)acetate (CAS RN 67634-00-8) with a purity by weight of 95 % --- Current product description: Allyl-(3-methylbutoxy)acetate (CAS RN 67634-00-8) | S | Amendment | UNDER EXAMINATION | NL | Applicant | Round 2025-07 - request for amendment.// |
| ex 2920 29 00 | 50 | 450636/2013 | 5020 | FR(29.08.2024): Fosetyl-aluminium (CAS RN 39148-24-8) with a purity by weight of 96 % or more --- Current product description: Fosetyl-aluminium (CAS RN 39148-24-8) | S | Amendment | UNDER EXAMINATION | FR | Applicant | Round 2025-07 - request for amendment.// >> Fosetyl-Aluminium is used into fungicides formulations |

| | | | | | | | | | | |
|---------------|----|------------|------|---|---|-----------|-------------------|----|-----------|---|
| ex 2925 11 00 | 20 | 462/2/1985 | 5007 | <p>DE(05.07.2024): 1,2-benzisothiazol-3(2H)-one 1,1-dioxide (Saccharin) CAS RN 81-07-2 with a purity by weight of 99 % or more and its derivatives 1,2-benzisothiazol-3(2H)-one 1,1-dioxide (sodium salt) CAS RN 128-44-9 with a purity by weight of 99 % or more</p> <p>*</p> <p>AT(12.09.2024): 1,2-benzisothiazol-3(2H)-one 1,1-dioxide, sodium salt (CAS RN 128-44-9) with a purity by weight of 99 % or more</p> <p>---</p> <p>Current product description: Saccharin and its sodium salt</p> | S | Amendment | UNDER EXAMINATION | DE | Applicant | |
| ex 2926 90 70 | 50 | 466/1/1991 | 5000 | <p>DE (27.08.2024): Ethylcyanoacetate (CAS RN 105-56-6) or Methyl cyanoacetate (CAS RN 105-34-0) with a purity by weight of 99,5 % or more</p> <p>*</p> <p>FR (04.07.2024): Ethyl cyanoacetate (CAS RN 105-56-6) with a purity by weight of 99,5 % or more</p> <p>---</p> <p>Current product description Alkyl or alkoxyalkyl esters of cyanoacetic acid</p> | S | Amendment | UNDER EXAMINATION | DE | Applicant | <p>Round 2025-07 - amendment Prolongation Exercise 2025-01-01 Prolongation Exercise 2024-01-01 Prolongation Exercise 2019-01-01 TARIC 2016: 2926 90 95 50 Round 1/1/2014: Proposal: the product under code 2926 9095 18 is already covered by suspension 2926 9095 50, therefore code 2926 9095 18 could be deleted SH 2002: 2926 90 95</p> |
| ex 2927 00 00 | 10 | 300/3/1991 | 5700 | <p>DE(21.06.2024): 2,2'-Dimethyl-2,2'-azodipropionamide dihydrochloride (CAS RN 2997-92-4) with a purity by weight of 97 % or more</p> | S | Amendment | UNDER EXAMINATION | DE | Applicant | <p>Round 2025-07 - request for amendment. Prolongation Exercise 2025-01-01</p> |

| | | | | | | | | | | |
|---------------|----|--------------------------|------|--|---|-----------|-------------------|----|-----------|--|
| | | | | <p>---</p> <p>Current description: 2,2'-Dimethyl-2,2'-azodipropionamide dihydrochloride (CAS RN 2997-92-4)</p> | | | | | | <p>Prolongation Exercise 2024-01-01</p> <p>Prolongation Exercise 2019-01-01</p> <p>Prolongation Exercise 1/1/2014</p> |
| ex 2927 00 00 | 30 | 572/6/1999 | 5021 | <p>FR (03.09.2024): 4'-Aminoazobenzene-4-sulphonic acid (CAS RN 104-23-4) with a purity by weight of 90 % or more</p> <p>---</p> <p>Current description: 4'-Aminoazobenzene-4-sulphonic acid (CAS RN 104-23-4)</p> | S | Amendment | UNDER EXAMINATION | BE | Applicant | <p>Round 2025-07 request for amendment.//</p> <p>Prolongation Exercise 2025-01-01</p> <p>Prolongation Exercise 2024-01-01</p> <p>Prolongation Exercise 2019-01-01</p> <p>Prolongation Exercise 1/1/2014</p> <p>SH 2002: 3824 90 95 --> 3824 90 99</p> <p>HS 2008</p> |
| ex 2931 49 80 | 48 | 1212/2009 1222/4/2003 | 5016 | <p>NL(29.08.2024): Tetrabutylphosphonium acetate (CAS RN 30345-49-4) in the form of an aqueous solution, containing by weight 40 % or more but not more than 50 % of tetrabutylphosphonium acetate</p> <p>---</p> <p>Current product description: Tetrabutylphosphonium acetate in the form of an aqueous solution (CAS RN 30345-49-4)</p> | S | Amendment | UNDER EXAMINATION | NL | Applicant | <p>Round 2025-07 - request for amendment.//</p> <p>Round 2025-01</p> <p>Prolongation Exercise, CN 2025 change Old CN 29314990, replaced with New CN 29314980.</p> <p>ROUND 2022/01</p> <p>New CN Code 29313990/ Old CN Code 29314990</p> <p>Prolongation Exercise 2020-01-01</p> <p>TARCI 2016: 2931 90 80 48</p> <p>SUSP 2015-01 / Prolong ex</p> |

| | | | | | | | | | | |
|---------------|----|------------|------|---|---|------------------|-------------------|-------|---------------------------|---|
| | | | | | | | | | | ROUND 01/2015 classification changed due to CN change as from 01/2015 TARIC 2014: 2931 90 90 89 TARIC 2011: 2931009989 |
| ex 2932 20 90 | 80 | 889/05 | 5056 | FR(11.09.2024): Gibberellic acid with a minimum purity by weight of 88 % (CAS RN 77-06-5) for use in the manufacture of plant protection products --- Current description: Gibberellic acid with a minimum purity by weight of 88 % (CAS RN 77-06-5) (1) | S | Amendment | UNDER EXAMINATION | IE PL | Applicant Co-applicant | Round 2024-07: request for amendment. Prolongation Exercise 2025-01-01 Prolongation Exercise 2024-01-01 Prolongation Exercise 2019-01-01 Prolongation Exercise 1/1/2014 TARIC 2011: 2932298580 |
| ex 2933 59 95 | 15 | 877/1/2004 | 5015 | NL(28.08.2024): Sitagliptin phosphate monohydrate (INN) (CAS RN 654671-77-9) with a purity by weight of 95 % --- Current product description: Sitagliptin phosphate monohydrate (CAS RN 654671-77-9) | S | Amendment | UNDER EXAMINATION | NL | Applicant | Round 2025-07 request for amendment.// Synonym of this product is Sitagliptin phosphate monohydrate. CAS number: 654671-77-9. Sitagliptin (CAS 486460-32-6) is mentioned in Annex 3 of the Combined Nomenclature. This is an INN product free of duty. Phosphate and hydrate are mentioned as suffix in Annex 4. |

| | | | | | | | | | | |
|---------------|----|--------------|------|--|---|-----------|-------------------|----|-----------|--|
| | | | | | | | | | | <p>This means that Sitagliptin phosphate monohydrate is also free of duty so a suspension should not be necessary.</p> <p>SEE: Annex 3 to CN - List of International Non-proprietary Names(INNs), provided for pharmaceutical substances by the World Health Organisation, which are free of duty</p> <p>Annex 4 to CN - List of prefixes and suffixes which, in combination with the INNs of Annex 3, describe the salts, esters or hydrates of INNs; these salts, esters and hydrates are free of duty, on condition that they are classifiable in the same 6-digit HS-subheading as the corresponding INN</p> |
| ex 3204 14 00 | 10 | 3058487/2014 | 5006 | Colourant C.I. Direct Black 80 (CAS RN 8003-69-8) and preparations based thereon with a colourant C.I. Direct Black 80 content of 90 % or more by weight | S | Amendment | UNDER EXAMINATION | IT | Applicant | Round 2025-07 - request for amendment. DG ENV question to IT from the previous round to be clarified. |

| | | | | | | | | | | |
|---------------|----|-------------|------|---|---|-----------|-------------------|----|-----------|--|
| | | | | | | | | | | Product used for colouring textile, leather and paper |
| 3301 12 10 | | 497/3/1995 | 5022 | <p>FR (06.09.2024): Essential oil of sweet orange (CAS RN 8028-48-6) or essential oil of sour orange (CAS RN 72968-50-4), not deterpenated</p> <p>---</p> <p>Current description: Essential oil of orange, not deterpenated</p> | S | Amendment | UNDER EXAMINATION | IE | Applicant | Round 2025-07 - request for amendment. / |
| ex 3402 90 10 | 20 | 1283/3/1983 | 5019 | <p>NL(29.08.2024): Mixture, containing by weight: - 80 % or more but not more than 90 % of docusate sodium (INN) (CAS RN 577-11-7), and - 10 % or more but not more than 20 % of sodium benzoate (CAS RN 532-32-1)</p> <p>---</p> <p>Current product description: Mixture of docusate sodium (INN) and sodium benzoate</p> | S | Amendment | UNDER EXAMINATION | NL | Applicant | Round 2025-07 - request for amendment.// |
| ex 3811 29 00 | 25 | 827274/2014 | 5023 | <p>FR (05.09.2024): Additives consisting of reaction products of C14-18 saturated and C18 unsaturated alcohols esterified with phosphorus pentoxide and salted with C12-14,-tert-alkylamines (CAS RN 1471315-74-8) for use in the manufacture of blends of additives for lubricating oils or greases</p> <p>---</p> <p>Current description: Additives containing at least salts of primary amines and mono- and di-alkylphosphoric acids, for use in the manufacture of lubricating oils or greases (1)</p> | S | Amendment | UNDER EXAMINATION | FR | Applicant | Round 2025-07 request for amendment./ Its main function is as an anti-wear agent and extreme pressure agent intended for further blending with other additives and lubricating oil base stocks to produce finished lubricants used primarily in gear oils and transmission fluids |

| | | | | | | | | | | |
|---------------|----|-------------|------|--|---|-----------|-------------------|----|-----------|---|
| ex 3811 29 00 | 35 | 827293/2014 | 5024 | <p>FR (05.09.2024): Reaction products of fatty acids, C14-C18 (branched and linear) and C18 (unsaturated) with tetraethylenepentamine (linear, branched, cyclic) (CAS RN 68784-17-8), for use in the manufacture of lubricating oils</p> <p>---</p> <p>Current description: Additives consisting of an imidazoline based mixture (CAS RN 68784-17-8), for use in the manufacture of lubricating oils (1)</p> | S | Amendment | UNDER EXAMINATION | FR | Applicant | <p>Round 2025-07 - request for amendment./</p> <p>>> It is therefore a chemical component that is added during the blending process to derive a further-processed final product. >>> In the various lubricating oil applications, the imported material provides cleanliness and friction modification to the formulated lubricating oil</p> |
| ex 3811 29 00 | 70 | 452903/2013 | 5025 | <p>FR (05.09.2024): Phosphonic acid, mixed C12-20-alkyl and C14-18-unsaturated alkyl derivatives (CAS 93925-25-8), containing more than 80 % by weight of oleyl, palmityl and stearyl groups, for use in the manufacture of lubricating oils</p> <p>---</p> <p>Current description: Additives consisting of dialkylphosphites (in which the alkyl groups contain more than 80 % by weight of oleyl, palmityl and stearyl groups), for use in the manufacture of lubricating oils (1)</p> | S | Amendment | UNDER EXAMINATION | FR | Applicant | <p>Round 2025-07 - request for amendment./</p> <p>The product consists of dialkyl phosphite typically of more than 90% by weight, with alkyl groups composed of a mix of: - C 18 monounsaturated, and - C 18 and C 16 saturated. The product has a semi-solid form at room temperature</p> |
| ex 3812 39 90 | 20 | 1301/6/1994 | 5747 | <p>DE(24.06.2024): Reaction mass of bis[2,2,6,6-tetramethyl-1-(octyloxy)piperidin-4-yl] decanedioate and 1,1'-bis[2,2,6,6-tetramethyl-1-(octyloxy)piperidin-4-yl]</p> | S | Amendment | UNDER EXAMINATION | DE | Applicant | <p>Round 2025-07 - request for amendment./</p> |

| | | | | | | | | | | |
|---------------|----|--------------|------|--|---|-----------|-------------------|----|-----------|---|
| | | | | <p>10,10'-{octane-1,8-diylbis[oxy(2,2,6,6-tetramethylpiperidine-1,4-diyl)]} didecanedioate (CAS RN 129757-67-1)</p> <p>---</p> <p>Current description: Mixture containing predominantly bis(2,2,6,6-tetramethyl-1-octyloxy-4-piperidyl) sebacate</p> | | | | | | |
| ex 3812 39 90 | 75 | 1806565/2023 | 5030 | <p>DE(27.08.2024): UV stabilizer consisting of a mixture of</p> <ul style="list-style-type: none"> - branched and linear C7 to C9 alkyl esters of [3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxy]-1-phenylpropanoic acid (CAS RN 127519-17-9) with a share of 85 % or more, and - 2-Methoxy-1-methylethyl acetate (CAS RN 108-65-6) containing not more than 8 % by weig <p>---</p> <p>Current description: UV stabilizer containing a mixture of:</p> <ul style="list-style-type: none"> - branched and linear C7 to C9 alkyl esters of [3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxy]-1- phenylpropanoic acid (CAS RN 127519-17-9) in an amount of 95 % by weight or more, and - 2-methoxy-1-methylethyl acetate (CAS RN 108-65-6) in an amount of not more than 5 % by weight | S | Amendment | UNDER EXAMINATION | DE | Applicant | Round 2025-07- request for amendment.// Round 2024/1 used for production of solvent-borne and specific waterborne coatings |
| ex 3812 39 90 | 85 | 1957248/2022 | 5031 | <p>DE(27.08.2025): Light stabilizer, reaction product of stearate methyl ester with 1-(2-hydroxy-2-methylpropoxy)-2,2,6,6-tetramethyl-4-piperidinol (CAS RN 300711-92-6) with a purity of more than 90 % by weight</p> <p>---</p> <p>Current description:</p> | S | Amendment | UNDER EXAMINATION | DE | Applicant | Round 2025-07 request for amendment.// Production of plastics that are particularly weather-resistant outdoors |

| | | | | | | | | | | |
|--------------------------------|----------|-------------|------|--|---|-----------|-------------------|----------|---------------------------|--|
| | | | | Light stabilizer, reaction product of stearic acid methyl ester with 1-(2-hydroxy-2-methylpropoxy)-2,2,6,6-tetramethyl-4-piperidinol (CAS RN 300711-92-6) with a purity of less than 90 % by weight | | | | | | |
| ex 3814 00 90 | 40 | 3114/5/04 | 5005 | <p>DG ENV: Reaction mass of 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane and 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluorobutane</p> <p>---</p> <p>Current text: Azeotrope mixtures containing isomers of nonafluorobutyl methyl ether and/or nonafluorobutyl ethyl ether</p> | S | Amendment | UNDER EXAMINATION | BE | Applicant | |
| ex 3824 99 92 | 32 | 230452/2009 | 5037 | <p>FR(13.09.2024): Mixture containing by weight: - 56 % or more but not more than 85 % of divi-nylbenzene-isomers (CAS 1321-74-0) - 15 % or more but not more than 44 % of ethylvi-nylbenzene-isomers (CAS 28106-30-1)</p> <p>---</p> <p>Current description: Mixture of divinylbenzene-isomers and ethylvinylbenzene-isomers, containing by weight 56 % or more but not more than 85 % of divinylbenzene (CAS RN 1321-74-0)</p> | S | Amendment | UNDER EXAMINATION | IT | Applicant | Round 2025-07 request for amendment.// |
| ex 3903 90 90 ex 3911 90 99 | 60 60 | 977359/2011 | 5018 | <p>NL(29.08.2024): Copolymer of styrene with maleic anhydride, either partially esterified or completely chemically modified, in flake or powder form</p> <p>---</p> <p>Current product description: Copolymer of styrene with maleic anhydride, either partially esterified or completely chemically</p> | S | Amendment | UNDER EXAMINATION | IE FR | Applicant Co-applicant | Round 2025-07 - request for amendment.// |

| | | | | | | | | | | |
|---------------|----|--------------|------|--|---|-----------|-------------------|-------|-------------------|---|
| | | | | modified, of an average molecular weight (Mn) of not more than 4500, in flake or powder form | | | | | | |
| ex 3911 90 19 | 15 | 1889490/2021 | 5017 | <p>NL(29.08.2024): Polyetherimide (CAS RN 61128-46-9, 61128-47-0, 77699-82-2, 96557-46-9, 99904-16-2, 1234673-19-8 or 2803979-49-7)</p> <p>or</p> <p>Polyetherimide of - 3,3'- or 4,4'-[(isopropylidene)bis(p-phenylenoxy)]diphthalic dianhydride and/or pyromellitic dianhydride, and - 1,3-benzenediamine and/or 1,4-benzenediamine and/or 4,4'-diamino diphenyl sulfone and/or 4,4'-(9H-fluoren-9-ylidene)bis benzenamine, and/or 4,4'-oxydianiline; whether or not with phthalic anhydride or amino-terminated polydimethylsiloxane endcaps (CAS RN 61128-46-9, 61128-47-0, 77699-82-2, 96557-46-9, 99904-16-2, 1234673-19-8 or 2803979-49-7)</p> <p>---</p> <p>Current product description: Polyetherimide of 4,4'-[(isopropylidene)bis(p-phenylenoxy)]diphthalic dianhydride and 1,3-benzenediamine or 1,4-benzenediamine (CAS RN 61128-46-9 or CAS RN 61128-47-0)</p> | S | Amendment | UNDER EXAMINATION | NL | Applicant | <p>Round 2025-07 - request for amendment.</p> <p>Round 2022-1 used in Automotive, Aerospace, Electrical, Healthcare, 5G and water management.</p> |
| ex 3920 10 89 | 55 | 246973/2011 | 5814 | <p>Ethylene vinyl acetate (EVA) film:</p> <ul style="list-style-type: none"> - with a raised relief surface with embossed undulations, - not laminated, - not cross-linked, and - with a thickness of more than 0,3 mm | S | Amendment | UNDER EXAMINATION | DE TR | Applicant Opposed | <p>Round 2025-07 - roll over./</p> <p>Round 2025-01 - objection.//</p> |
| ex 6804 21 00 | 30 | 6660034/2023 | 5038 | <p>TR(17.09.2024): Steel wire used for cropping and squaring semiconductors:</p> | S | Amendment | UNDER EXAMINATION | TR | Applicant | <p>Round 2025-07 Request for amendment.//</p> |

| | | | | | | | | | | |
|--------------------------------|----------|--------------|------|--|---|------------------|-------------------|----|-----------|---|
| | | | | <ul style="list-style-type: none"> - coated with diamond grains of 5µm or more, but not more than 55µm, - wire diameter 23 µm or more but not exceeding 350 µm, - a breaking strength of 11 N or more, but not exceeding 170 <p>---</p> <p>Steel wire used for cropping and squaring semiconductors:</p> <ul style="list-style-type: none"> - coated with diamond grains of 5 µm or more but not more than 55 µm, - with a wire diameter of 45 µm or more, but not more than 370 µm, - a breaking strength of 11,5 N or more but not more than 200 N | | | | | | steel wire for solar module |
| ex 8501 31 00 ex 8501 32 00 | 63 65 | 3812069/2015 | 5050 | <p>DE (27.08.2024): Ready for installation in vehicles or equipment of headings 8432 and 8433, brushless and permanently excited direct current motor with:</p> <ul style="list-style-type: none"> - a specified speed of not more than 6000 rpm, - a minimum output of 400 W, but not more than 1,3 kW (at 12 V), or with a minimum output of 750 W but not more than 1,55 kW (at 36 V), - a flange diameter of 85 mm or more but not more than 200 mm, - a maximum length of 335 mm, measured from the beginning of the shaft to the outer ending, - a housing length of not more than 265 mm, measured from the flange to the outer ending, - a maximum of two-piece (basic housing including electric components and flange with minimum 2 and maximum 11 bore holes) aluminium diecast or sheet steel housing whether or not with a sealing compound (groove with an O-ring and grease), - a stator with single T-tooth design and single coil windings in 9/6 or 12/8 or 12/10 topology, and | S | Amendment | UNDER EXAMINATION | DE | Applicant | Round 2025-07 - request for amendment.// brushless, permanent-magnet synchronous motor |

| | | | | | | | | | | |
|--------------------------------|----|--------------|------|--|---|------------------|-------------------|----|-----------|-------------------------------------|
| | | | | <ul style="list-style-type: none"> - surface magnets, - whether or not with electronic power steering controller, - whether or not with pulley or coupling , - whether or not with rotor position sensor <p>---</p> <p>Current description: Ready for installation in vehicles or equipment of headings 8432 and 8433, brushless and permanently excited direct current motor with:</p> <ul style="list-style-type: none"> - a specified speed of not more than 4 100 rpm, - a minimum output of 400 W, but not more than 1,3 kW (at 12 V), or with a minimum output of 750 W but not more than 1,55 kW (at 36 V), - a flange diameter of 85 mm or more but not more than 200 mm, - a maximum length of 335 mm, measured from the beginning of the shaft to the outer ending, - a housing length of not more than 265 mm, measured from the flange to the outer ending, - a maximum of two-piece (basic housing including electric components and flange with minimum 2 and maximum 11 bore holes) aluminium diecast or sheet steel housing whether or not with a sealing compound (groove with an O-ring and grease), - a stator with single T-tooth design and single coil windings in 9/6 or 12/8 topology, and - surface magnets, - whether or not with electronic power steering controller, - whether or not with pulley, - whether or not with rotor position sensor | | | | | | |
| ex 8501 51 00 ex 8501 52 20 | 60 | 1952918/2023 | 5004 | DE(27.08.2024): Automotive-ready brushless permanently excited magnet synchronous AC-motor with: | S | Amendment | UNDER EXAMINATION | DE | Applicant | Round 2025/7 request for amendment. |

| | | | | | | | | | | |
|--|----|--|--|--|--|--|--|--|--|--|
| | 60 | | | <ul style="list-style-type: none"> - a specified speed of not more than 7000 rpm, - a power rating of 400 W or more but not more than 1,8 kW (at 12 V), - a flange diameter of 80 mm or more, but not more than 200 mm, - a maximum length of not more than 335 mm, measured from the beginning of the shaft to its outer end, - a housing length of not more than 265 mm, measured from the flange to the outer end, - a steel sheet or die-cast aluminium basic housing consisting of not more than two parts, including electrical components and a flange with two or more but not more than 11 holes, whether or not with a sealing connection (groove with O-ring and protective grease or liquid seal interface), - a stator with single T-tooth design and single coil winding with 9/6 or 12/10 or 12/8 topology and surface magnets - whether or not with electronic power steering controller, - whether or not with pulley or coupling, - whether or not with rotor position sensor <p>---</p> <p>Current text: Automotive-ready brushless permanently excited magnet synchronous AC-motor with</p> <ul style="list-style-type: none"> - a specified speed of not more than 7 000 rpm, - a power rating of 400 W or more but not more than 1,8 kW (at 12 V), - a flange diameter of 80 mm or more, but not more than 200 mm, - a maximum length of not more than 220 mm, measured from the beginning of the shaft to its outer end, - a housing length of not more than 180 mm, measured from the flange to the outer end, - a steel sheet or die-cast aluminium basic housing consisting of not more than two parts, | | | | | | Round 2024/1 used for production of vehicles |
|--|----|--|--|--|--|--|--|--|--|--|

| | | | | | | | | | | |
|---------------|----|--------------|------|--|---|------------------|-------------------|----|-----------|---|
| | | | | <p>including electrical components and a flange with two or more but not more than 11 holes, whether or not with a sealing connection (groove with O-ring and protective grease or liquid seal interface),</p> <ul style="list-style-type: none"> - a stator with single T-tooth design and single coil winding with 12/10 or 12/8 topology and surface magnets | | | | | | |
| ex 8503 00 98 | 53 | 6650648/2023 | 5051 | <p>PL(11.09.2024): Pressure casted rotor cover of the cooling channel system in the electrical motor:</p> <ul style="list-style-type: none"> - of EN AC-47100-F aluminum, - with a sealing cap of stainless steel, - shot-blasted and machined, - leakproof to the degree of 1 ml per minute or less under 2,75 bar pressure, - with a hardness of 70 HBW or more (2,5/62,5, according to ISO 6506), - with a tensile strength of 190 N/mm² or more, - with a height of 42 mm or more, but not more than 64 mm, - with a diameter of 88 mm or more, but not more than 132 mm, - with a weight of 0,3 kg or more but not more than 0,5 kg <p>---</p> <p>Current description: Pressure casted rotor cover of the cooling channel system in the electrical motor:</p> <ul style="list-style-type: none"> - of EN AC-47100-F aluminum, - with a sealing cap of stainless steel, - shot-blasted and machined, - leakproof to the degree of 1 ml per minute or less under 2,75 bar pressure, - with a hardness of 70 HBW or more (2,5/62,5, according to ISO 6506), - with a tensile strength of 240 N/mm² or more, - with a height of 50 mm or more, but not more than 55 mm, | S | Amendment | UNDER EXAMINATION | PL | Applicant | <p>Round 2025-07: request for amendment.//</p> <p>- used for the manufacture of electrical motors</p> |

| | | | | | | | | | | |
|---------------|----|--------------|------|--|---|-----------|-------------------|----|-----------|---|
| | | | | <ul style="list-style-type: none"> - with a diameter of 109 mm or more, but not more than 112 mm, - with a weight of 3,9 kg or more but not more than 4,2 kg | | | | | | |
| ex 8503 00 98 | 58 | 6647017/2023 | 5052 | <p>PL(11.09.2024): Pressure casted inner housing of a cooling channel system for an electrical motor:</p> <ul style="list-style-type: none"> - of EN AC-47100 aluminum, - shot-blasted and machined, - leakproof to the degree of 3 ml per minute or less under 2,75 bar pressure, - with a hardness of 70 HBW or more (2,5/62,5, according to ISO 6506) - with a tensile strength of 190 N/mm² or more, - with a height of 160 mm or more, but not more than 330 mm, - with a diameter of 240 mm or more, but not more than 368 mm, - with a weight of 3 kg or more, but not more than 5,84 kg <p>---</p> <p>Current description: Pressure casted inner housing of a cooling channel system for an electrical motor:</p> <ul style="list-style-type: none"> - of EN AC-47100 aluminum, - shot-blasted and machined, - leakproof to the degree of 3 ml per minute or less under 2,75 bar pressure, - with a hardness of 70 HBW or more (2,5/62,5, according to ISO 6506) - with a tensile strength of 240 N/mm² or more, - with a height of 225 mm or more, but not more than 280 mm, - with a diameter of 300 mm or more, but not more than 310 mm, - with a weight of 3,8 kg or more, but not more than 4,9 kg | S | Amendment | UNDER EXAMINATION | PL | Applicant | <p>Round 2025-07: request for amendment.</p> <p>for use in the manufacture of electrical motors</p> |

| | | | | | | | | | | |
|---------------|----|--------------|------|--|---|-----------|-------------------|----|-----------|--|
| ex 8503 00 98 | 63 | 6647219/2023 | 5055 | <p>PL (11.09.2024): Pressure casted outer housing of an electrical motor:</p> <ul style="list-style-type: none"> - of EN AC-47100 aluminum, - with or without overmolded bearing sleeves of martensitic stainless steel and assembled sealing caps of stainless steel, - shot-blasted and machined, - with or without a rotor chamber, leakproof to the degree of 3 ml per minute or less under 2,75 bar pressure, - with a hardness of 70 HBW or more (2,5/62,5, according to ISO 6506) - with a tensile strength of 190 N/mm² or more, - with a height of 195 mm or more, but not more than 430 mm, - with a width of 290 mm or more, but not more than 625 mm, - with a length of 270 mm or more, but not more than 535 mm, - with a weight of 5,2 kg or more, but not more than 12,5 kg <p>---</p> <p>Current description: Pressure casted outer housing of an electrical motor:</p> <ul style="list-style-type: none"> - of EN AC-47100 aluminum, - with overmolded bearing sleeves of martensitic stainless steel and assembled sealing caps of stainless steel, - shot-blasted and machined, - a rotor chamber, leakproof to the degree of 3 ml per minute or less under 2,75 bar pressure, - with a hardness of 70 HBW or more (2,5/62,5, according to ISO 6506) - with a tensile strength of 240 N/mm² or more, - with a height of 245 mm or more, but not more than 360 mm, | S | Amendment | UNDER EXAMINATION | PL | Applicant | Round 2025-07:request for amendment./ for manufacturing electrical motors |
|---------------|----|--------------|------|--|---|-----------|-------------------|----|-----------|--|

| | | | | | | | | | | |
|---------------|----|--------------|-------|--|---|------------------|-------------------|----------------------|--|--|
| | | | | <ul style="list-style-type: none"> - with a width of 360 mm or more, but not more than 525 mm, - with a length of 345 mm or more, but not more than 450 mm, - with a weight of 6,4 kg or more, but not more than 8,3 kg | | | | | | |
| ex 8507 60 00 | 26 | 6609698/2023 | 5010B | <p>IT(27.08.2024): Modules for the assembly of electric accumulators using lithium ferrophosphate technology (LFP) with:</p> <ul style="list-style-type: none"> - a length of 670 mm or more, but not more than 882 mm, - a width of 390 mm or more, but not more than 655 mm, - a height of 110 mm or more, but not more than 137 mm, - a weight of 60 kg or more, but not more than 165 kg, and - a power of 11 300 Wh or more, but not more than 29 360 Wh <p>---</p> <p>Current text: Modules for the assembly of electric accumulators using lithium ferrophosphate technology (LFP) with:</p> <ul style="list-style-type: none"> - a length of 820 mm or more, but not more than 882 mm, - a width of 390 mm or more, but not more than 655 mm, - a height of 110 mm or more, but not more than 137 mm, - a weight of 60 kg or more, but not more than 165 kg, and - a power of 11 300 Wh or more, but not more than 29 360 Wh | S | Amendment | UNDER EXAMINATION | DE EU EU | Applicant Opposed Opposed | Round 2025/07 request for amendment. used for assembly of ion lithium electric accumulators, which will be incorporated in battery electric vehicles. |
| ex 8507 60 00 | 48 | 4922932/2020 | 5011B | <p>IT(27.08.2024) request for amendment: Integrated battery system in a metal/plastic case with or without holders, consisting of:</p> | S | Amendment | UNDER EXAMINATION | CZ EU EU EU | Applicant Opposed Opposed Opposed | Round 2025-01 - review of the suspension |

| | | | | | | | | | | |
|--|--|--|--|---|--|--|--|----|---------|--|
| | | | | <ul style="list-style-type: none"> - a lithium-ion battery with a voltage of 36 V or more but not more than 50,4 V and a nominal energy between 0,3kWh and 0,9 kWh, - Battery Management System, - a power relay, - a cooling system, - one to four connectors, <p>for use in the manufacture of Mild-hybrid (mHEV) motor vehicles</p> <p>---</p> <p>Current text: Integrated battery system in a metal case with holders, consisting of:</p> <ul style="list-style-type: none"> - a lithium-ion battery with a voltage of 36 V or more but not more than 50,4 V and a nominal energy of 0,6 kWh, - Battery Management System, - a power relay, - a cooling system, - four connectors, <p>for use in the manufacture of Mild-hybrid (mHEV) motor vehicles</p> <p>(1)</p> | | | | EU | Opposed | Integrated battery system in a metal case with holders |
|--|--|--|--|---|--|--|--|----|---------|--|

(1) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013.

DISCLAIMER: The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group. Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic.